


**NASA CONTRACTOR
REPORT**



NASA CR-2320

NASA CR-2320

**THE INFLUENCE OF WING LOADING
ON TURBOFAN POWERED STOL TRANSPORTS
WITH AND WITHOUT EXTERNALLY BLOWN FLAPS**

*by R. L. Morris, C. R. Hanke, L. H. Pasley,
and W. J. Rohling*

Prepared by

THE BOEING COMPANY

WICHITA DIVISION

Wichita, Kans. 67210

for Langley Research Center

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION • WASHINGTON, D. C. • NOVEMBER 1973

| | | | | | |
|--|--|--|--|--|--|
| 1. Report No. NASA CR-2320 | | 2. Government Accession No. | | 3. Recipient's Catalog No. | |
| 4. Title and Subtitle The Influence of Wing Loading on Turbofan Powered STOL Transports With and Without Externally Blown Flaps | | | | 5. Report Date November 1973 | |
| | | | | 6. Performing Organization Code - | |
| 7. Author(s) R. L. Morris, C. R. Hanke, L. H. Pasley, and W. J. Rohling | | | | 8. Performing Organization Report No. D3-8514-7 | |
| 9. Performing Organization Name and Address The Boeing Company Wichita Division Wichita, KS | | | | 10. Work Unit No. 741-86-03-03 | |
| | | | | 11. Contract or Grant No. NAS1-11370 | |
| | | | | 13. Type of Report and Period Covered Contractor Report | |
| 12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546 | | | | 14. Sponsoring Agency Code | |
| | | | | | |
| 15. Supplementary Notes This is a final report. | | | | | |
| 16. Abstract The effects of wing loading on the design of short takeoff and landing (STOL) transports using (1) mechanical flap systems, and (2) externally blown flap systems are determined. Aircraft incorporating each high-lift method are sized for Federal Aviation Regulation (F.A.R.) field lengths of 2,000 feet, 2,500 feet, and 3,500 feet, and for payloads of 40, 150, and 300 passengers, for a total of 18 point-design aircraft. An assumed 1975 level of technology is applied to both concepts in terms of propulsion, weights, active controls, supercritical wing methodology, and acoustics. Low-wing-loading STOL configurations with mechanical flaps are found to be competitive with externally blown flap STOL configurations over wide ranges of payload and field length for the airworthiness rules and technology improvements assumed. Because the results of design studies like this one are sensitive to the ground rules assumed, careful attention is paid to describing the assumptions. These assumptions must be understood before the results are compared with other STOL airplane studies. | | | | | |
| 17. Key Words (Suggested by Author(s)) STOL, Low Wing Loading | | | | 18. Distribution Statement Unclassified - Unlimited | |
| 19. Security Classif. (of this report) Unclassified | | 20. Security Classif. (of this page) Unclassified | | 21. No. of Pages 164 | |
| | | | | 22. Price* Domestic, \$4.75 Foreign, \$7.25 | |

TABLE OF CONTENTS

| | <u>PAGE</u> |
|---|-------------|
| 1.0 SUMMARY | 1 |
| 2.0 INTRODUCTION | 3 |
| 3.0 SYMBOLS | 5 |
| 4.0 1975 TECHNOLOGY ASSUMPTIONS | 13 |
| 4.1 PROPULSION SYSTEM | 13 |
| 4.2 WEIGHTS METHODOLOGY | 14 |
| 4.2.1 GUST LOAD ALLEVIATION SYSTEM WEIGHTS | 17 |
| 4.2.2 GROUP WEIGHT STATEMENT | 20 |
| 4.2.3 FINAL WEIGHT STATEMENT | 27 |
| 4.3 AERODYNAMICS | 27 |
| 4.3.1 SUPERCRITICAL WING METHODOLOGY | 27 |
| 4.3.2 HIGH SPEED DRAG ESTIMATION | 29 |
| 4.3.3 HIGH SPEED AERODYNAMIC CHARACTERISTICS | 34 |
| 4.3.4 LOW SPEED AERODYNAMIC CHARACTERISTICS | 35 |
| 5.0 TAKEOFF AND LANDING | 39 |
| 5.1 TAKEOFF RULES AND PROCEDURE | 39 |
| 5.2 LANDING RULES AND PROCEDURE | 42 |
| 6.0 VERTICAL TAIL SIZING | 47 |
| 6.1 MECHANICAL FLAP CONFIGURATION VERTICAL TAIL SIZE | 50 |
| 6.2 EXTERNALLY BLOWN FLAP CONFIGURATION VERTICAL TAIL SIZE | 54 |
| 7.0 HORIZONTAL TAIL SIZING | 59 |
| 7.1 MECHANICAL FLAP CONFIGURATION HORIZONTAL TAIL SIZE | 61 |
| 7.2 EXTERNALLY BLOWN FLAP CONFIGURATION HORIZONTAL TAIL SIZE | 62 |
| 8.0 CONFIGURATION DEVELOPMENT | 67 |
| 8.1 MISSION | 67 |
| 8.2 FUSELAGES | 69 |
| 8.3 MECHANICAL FLAP CONFIGURATION WING DEVELOPMENT | 69 |
| 8.4 AIRPLANE PERFORMANCE AND SIZING | 72 |
| 8.4.1 MECHANICAL FLAP CONFIGURATION DESIGN CONSTRAINTS | 72 |
| 8.4.2 EXTERNALLY BLOWN FLAP CONFIGURATION DESIGN CONSTRAINTS | 75 |
| 8.5 STOL TRANSPORT SIZE COMPARISON | 75 |
| 8.6 3-VIEWS | 75 |

TABLE OF CONTENTS (CONT'D)

| | <u>PAGE</u> |
|---|-------------|
| 8.7 SENSITIVITIES | 91 |
| 8.7.1 GUST LOAD ALLEVIATION | 91 |
| 8.7.2 ALTITUDE | 91 |
| 8.7.3 CRUISE MACH NUMBER | 92 |
| 9.0 NOISE | 97 |
| 9.1 ESTIMATION METHODOLOGY | 97 |
| 9.2 ATTENUATION | 99 |
| 10.0 DIRECT OPERATING COST | 103 |
| 11.0 CONCLUDING REMARKS | 109 |
| 12.0 APPENDICES | 111 |
| 12.1 APPENDIX A – WEIGHT STATEMENTS | 111 |
| 12.2 APPENDIX B – HIGH SPEED DRAG POLARS | 130 |
| 12.3 APPENDIX C – DETERMINATION OF EBF WING LOADING AND THRUST TO WEIGHT RATIO | 149 |
| 12.4 APPENDIX D – WEIGHT AND BALANCE | 154 |
| 13.0 REFERENCES | 161 |

THE INFLUENCE OF WING LOADING
ON TURBOFAN POWERED STOL TRANSPORTS
WITH AND WITHOUT
EXTERNALLY BLOWN FLAPS – FINAL REPORT

BY
R. L. MORRIS
C. R. HANKE
L. H. PASLEY
W. J. ROHLING

1.0 SUMMARY

The objective of this study was to determine the effects of wing loading on the design of short takeoff and landing (STOL) transports using (1) mechanical flap systems, and (2) externally blown flap systems. Aircraft incorporating each high-lift method were sized for Federal Aviation Regulation (F.A.R.) field lengths of 2,000 feet, 2,500 feet, and 3,500 feet, and for payloads of 40, 150, and 300 passengers, for a total of 18 point-design aircraft. An assumed 1975 level of technology was applied to both concepts in terms of propulsion, weights, active controls, supercritical wing methodology, and acoustics.

The objective of this study was to determine if low-wing-loading short takeoff and landing (STOL) transports with mechanical flaps (MF) are competitive with externally blown flap (EBF) configurations. Aircraft incorporating each high lift method were sized for Federal Aviation Regulation (F.A.R.) field lengths of 2,000 feet, 2,500 feet and 3,500 feet, and for payloads of 40, 150 and 300 passengers for a total of 18 point design aircraft.

Throughout the study every effort was made to evaluate the two concepts on a common basis, so that a true comparison would emerge. An assumed 1975 level of technology was applied to both concepts in terms of propulsion, weights, supercritical wing methodology and acoustics.

All airplanes were sized for the same mission (.8 Mach cruise speed) using the same engine technology. Weight estimating methods were identical except for weight scaling of the flaps and flap tracks for the EBF configurations.

An important factor in this study was the assumption that an active gust load alleviation (GLA) system was incorporated on all airplanes. The benefits of such a system are structural weight reduction due to limitation of design gust loads to 2.5 g's and ride smoothing.

In the absence of F.A.R.'s for powered lift configurations a set of takeoff, approach and go-around safety margins were developed so that the EBF airplane takeoff and landing performance would be comparable to the MF airplane. Low speed aerodynamic characteristics for the MF configurations were developed from empirical and theoretical high lift data. Low speed aerodynamic characteristics for the EBF airplanes were based on NASA wind tunnel data.

Supercritical wing technology was assumed for both concepts. Wing thickness was determined so both MF and EBF configurations would have the same wing drag divergence Mach number.

A specific noise criteria was not a constraint of the study. However, an equivalent level of noise attenuation was applied to both concepts, except that a 10 dB noise increase was assigned to the EBF configurations due to the under wing blowing.

The two concepts were compared primarily on a gross weight basis. In addition, a noise and direct operating cost (DOC) comparison was made for selected design point airplanes. For the range of field lengths and payloads investigated the MF configurations were lighter, quieter and more economical than the EBF configurations. Gust load alleviation provides a large weight savings for airplanes with field lengths shorter than 2,500 feet. This improvement is greater for the MF configurations.

Because the results of design studies like this one are sensitive to the ground rules assumed, careful attention has been paid to describing the assumptions. These assumptions must be understood before the results are compared with other STOL airplane studies.

2.0 INTRODUCTION

A large number of STOL airplane aerodynamic configuration studies have been performed to examine various powered lift concepts. Most of these studies indicated that wing loadings in the neighborhood of 100 lbs/ft² were desired to provide high speed cruise performance and acceptable ride. A study was completed in 1971 for NASA by Boeing-Wichita, Reference 1, on a 130 passenger, 2,000 foot F.A.R. field length configuration. Results of the study are also presented in Reference 2. This study showed that by utilizing modern control system technology to provide ride smoothing, a low-wing-loading (50 lbs/ft²) 2,000 foot field length STOL airplane appeared competitive with a high-wing-loading powered lift design, (airplane model 751 of Reference 1). Because powered lift was not relied upon, the configuration which resulted offered advantages in system simplicity, reliability and safety.

The objective of the current study was to:

- Determine the effects of wing loading on the design of larger and smaller airplanes than the referenced configuration.
- Compare the mechanical flap and externally blown flap concepts as field length and payload vary.

STOL transports were sized for payloads of 40, 150 and 300 passengers for F.A.R. field lengths of 2,000 feet, 2,500 feet and 3,500 feet. The airplanes were sized for a mission consisting of three unrefueled 250 nautical mile hops plus reserves, the cruise portion of which was flown at $M = .8$ at 35,000 feet. The airplanes were first sized considering low-wing-loading, which for the purpose of this study is defined as achieving STOL performance from mechanical flaps (MF). Airplanes were then sized with externally blown flaps (EBF) resulting in a total of 18 point design aircraft. To assist in evaluating the merits of each configuration, the direct operating costs and noise aspects of selected point design airplanes were determined.

Initially the ground rules and assumptions for a 1975 level of technology were established followed by the development of the wing planform for the MF configuration. Takeoff and landing design constraints were determined and tail sizing criteria were established prior to sizing of the 18 point design airplanes. Finally, a comparison of the 18 airplanes was made on a gross weight basis without the weight penalties associated with noise attenuation. One iteration was made on selected design point aircraft to determine the gross weight penalty which would result from noise suppression. Direct operating costs (DOC) were determined and DOC sensitivity trade studies were accomplished.

Page intentionally left blank

3.0 SYMBOLS

| | | |
|---------------------------|---|---|
| ΔP_I | – | Change in functional area for a particular fuselage segment |
| AR | – | Aspect ratio |
| A_{WET} | – | Wetted area, m^2 (ft^2) |
| a_H | – | Horizontal tail lift curve slope, per deg. |
| a_V | – | Vertical tail lift curve slope, per deg. |
| a_{WB} | – | Wing-body lift curve slope, per deg. |
| BPR | – | Engine by-pass ratio |
| b | – | Wing span, m (ft) |
| C_{AF} | – | Aft flap chord, percent local chord |
| C_D | – | Airplane drag coefficient |
| $C_{D_{FLAPS\ DOWN}}$ | – | Airplane flaps-down drag coefficient |
| C_{D_i} | – | Induced drag coefficient |
| C_{D_f} | – | Skin friction drag coefficient based on wing reference area |
| C_{D_0} | – | Zero lift or parasite drag coefficient with no compressibility |
| $C_{D_{P_{MIN\ CRUISE}}}$ | – | Cruise configuration minimum parasite drag coefficient |
| C_f | – | Skin friction drag coefficient based on wetted area |
| CG | – | Airplane center of gravity as a fraction of wing aerodynamic center |
| C_L | – | Airplane lift coefficient |
| C_{LE} | – | Leading edge flap chord, percent local chord |
| $C_{L_{APP}}$ | – | Airplane approach lift coefficient |

| | |
|-----------------|---|
| $C_{L\alpha}$ | — Airplane lift curve slope, per deg |
| C_{LH} | — Horizontal tail lift coefficient |
| $C_{L\delta}$ | — Lift coefficient for minimum wing twist factor |
| C_{LMAX} | — Maximum lift coefficient |
| C_{LV} | — Vertical tail lift coefficient |
| C_{LVMIN} | — Airplane lift coefficient corresponding to minimum flight speed |
| C_{LS} | — Airplane lift coefficient corresponding to stall speed |
| C_{LWB} | — Wing-body lift coefficient |
| $C_{l\beta}$ | — Rolling moment coefficient due to sideslip, per deg. |
| C_{MF} | — Main flap chord, percent local chord |
| C_M | — Pitching moment coefficient |
| C_{M0WB} | — Wing-body pitching moment coefficient at zero lift |
| $C_{n\beta}$ | — Yawing moment coefficient due to sideslip, per deg. |
| $C_{n\beta V}$ | — Vertical tail yawing moment coefficient due to sideslip, per deg. |
| $C_{n\beta WB}$ | — Wing-body yawing moment coefficient due to sideslip, per deg. |
| C_p | — Pressure coefficient, $\frac{\Delta P}{q}$ |
| C_T | — Thrust coefficient, $\frac{T}{qS}$ |
| $C_{TMAX.}$ | — Maximum thrust coefficient, $\frac{T_{MAX}}{qS}$ |

| | |
|-----------------|---|
| c | — Chord, m (in) |
| c_d | — Two dimensional drag coefficient |
| c_l | — Two dimensional lift coefficient |
| \bar{c} | — Wing mean aerodynamic chord, m (in) |
| D | — Drag and diameter, newtons (lb), m (ft) |
| DL_i | — Change in fuselage diameter over the change in length of each fuselage segment |
| D_{RAM} | — Engine ram drag, newtons (lb) |
| dB | — Decibel |
| EBF | — Externally blown flap |
| F_N | — Scaled engine sea level static thrust, newtons (lb) |
| F_{NREF} | — Reference engine sea level static thrust, newtons (lb) |
| f | — Frequency, Hz |
| GLA | — Gust load alleviation |
| g | — Acceleration of gravity, m/sec^2 (ft/sec^2) |
| I_{ZZ} | — Airplane yaw moment of inertia, $kg - m^2$ ($slug - ft^2$) |
| i_T | — Horizontal tail incidence, deg. |
| KB_i | — Fuselage wave drag factor |
| K_f | — Interference and tolerance factor for adjustment of skin friction drag |
| $(L/D)_{EQUIV}$ | — Equivalent lift-to-drag ratio |
| l_B | — Fuselage length, m (ft) |
| l_H | — Horizontal tail arm measured from the wing aerodynamic center to the horizontal tail aerodynamic center, m (in) |
| l_V | — Vertical tail arm measured from the wing aerodynamic center to the vertical tail aerodynamic center, m (in) |
| M | — Free stream Mach number |

| | | |
|--------------|---|--|
| M_{2D} | — | Two dimensional Mach number |
| M_{3D} | — | Three dimensional Mach number |
| M_{DD} | — | Airplane drag divergence Mach number |
| M_{DDc} | — | Drag divergence Mach number of a 1969 technology wing |
| M_{DDWING} | — | Wing drag divergence Mach number |
| M_L | — | Local Mach number |
| M_O | — | Free stream Mach number for which compressibility drag begins to develop on the body |
| M_p | — | Free stream Mach number for which maximum compressibility drag has developed on the body |
| MF | — | Mechanical flap |
| N | — | Number of engines |
| NOY | — | Unit of perceived noisiness |
| n | — | Load factor |
| OWE | — | Operating weight empty, newtons (lb) |
| PNL | — | Perceived noise level |
| q | — | Dynamic pressure kg/m^2 (lb/ft ²) |
| S | — | Wing area, m^2 (ft ²) |
| S_B | — | Body cross sectional area, m^2 (ft ²) |
| SFC | — | Engine specific fuel consumption |
| SPL | — | Sound pressure level |
| S_H | — | Horizontal tail area, m^2 (ft ²) |
| S_{REF} | — | Reference area, m^2 (ft ²) |
| S_V | — | Vertical tail area, m^2 (ft ²) |
| T | — | Thrust, newtons (lb) |

| | | |
|--------------|---|--|
| T_{BL} | – | Blowing thrust, newtons (lb) |
| T_{PRIM} | – | Direct thrust which does not interact with lift and drag, newtons (lb) |
| T_{REF} | – | Reference thrust, newtons (lb) |
| T_{STATIC} | – | Static thrust, newtons (lb) |
| t/c | – | Wing thickness ratio, fractional part of local chord |
| V_{APP} | – | Aircraft approach speed, knots |
| V_{CW} | – | Cross wind component perpendicular to aircraft flight path, knots |
| V_e | – | Equivalent airspeed, knots |
| \bar{V}_H | – | Horizontal tail volume coefficient |
| V_{JET} | – | Jet velocity, m/sec (ft/sec) |
| V_{LOF} | – | Airplane lift off speed, knots |
| V_{MC} | – | Airplane engine out minimum control speed, knots |
| V_{MCG} | – | Airplane engine out ground minimum control speed knots |
| V_{MU} | – | Airplane minimum unstick speed, knots |
| V_{MO} | – | Airplane maximum operational speed, knots |
| V_R | – | Airplane takeoff rotation speed, knots |
| V_S | – | Airplane stall speed, knots |
| \bar{V}_V | – | Vertical tail volume coefficient |
| V_1 | – | Critical engine failure speed, knots |
| V_2 | – | Takeoff climb speed, knots |
| V_{2OEI} | – | Takeoff climb speed with one engine inoperative, knots |
| W | – | Gross weight, newton (lb) |

| | | |
|-------------------------------|---|--|
| $X_{AC_{WB}}$ | — | Wing body aerodynamic center measured relative to the mean aerodynamic chord, m (in) |
| X_{CG} | — | Center of gravity measured relative to the mean aerodynamic chord, m (in) |
| X/C | — | Fractional percent of local chord measured along the chord |
| X_{MG} | — | Main landing gear location measured relative to the mean aerodynamic chord, m (in) |
| y_e | — | Critical engine moment arm, m (in) |
| Z_T | — | Engine pitching moment arm, m (in) |
| α_{APP} | — | Angle of attack at approach lift coefficient, deg. |
| α_S | — | Stall angle of attack, deg. |
| γ | — | Flight path angle, deg. |
| $\Delta\alpha$ | — | Incremental angle of attack, deg. |
| $\Delta C_{D_{iTE}}$ | — | Induced drag of leading edge flaps |
| ΔC_{D_M} | — | Drag rise due to compressibility |
| $\Delta C_{D_{MB}}$ | — | Fuselage drag rise due to compressibility |
| ΔC_{D_P} | — | Drag correction for variation from parabolic polar, clean wing |
| $\Delta C_{D_{P_{MIN_{LE}}}}$ | — | Parasite drag of leading edge flap |
| $\Delta C_{D_{P_{MIN_{TE}}}}$ | — | Parasite drag of trailing edge flap |
| Δg | — | Change in load factor |
| ΔM_{TECH} | — | Mach number technology correction for wing design technology other than M_{DDC} |

| | | |
|--------------------------|---|--|
| Δ_{M_t} | — | Mach number thickness correction |
| Δ_{M_Λ} | — | Mach number sweep correction |
| δ_{CDP} | — | Drag correction for variation from parabolic polar with leading and trailing edge flaps down |
| δ_{CRAB} | — | Crab angle of landing gear relative to the ground velocity vector at touchdown, deg. |
| δ_F | — | Wing flap angle, deg. |
| δ_O | — | Nonelliptic factor for untwisted wings |
| δ / δ_O | — | Twist factor |
| η | — | Percent semispan |
| θ_{AEO} | — | Pitch attitude with all engines operating, deg. |
| θ_{OEI} | — | Pitch attitude with outboard engine inoperative, deg. |
| Λ | — | Sweep angle, deg. |
| $\Lambda_{c/4}$ | — | Sweep of quarter chord, deg. |
| Λ_{EFF} | — | Effective wing sweep angle, deg. |
| λ | — | Wing taper ratio |
| ρ | — | Atmospheric density, kg/m^3 (slugs/ft ³) |
| ω_{nDR} | — | Dutch roll natural frequency, 1/sec |
| $\frac{d\sigma}{d\beta}$ | — | Change in sidewash with respect to sideslip |

Page intentionally left blank

4.0 1975 TECHNOLOGY ASSUMPTIONS

This section discusses the background and details of assumed 1975 technology in terms of propulsion, weights, gust load alleviation (GLA) system weight, supercritical wing methodology, lift and drag.

Propulsion system improvements anticipated for 1975 technology advancement were applied to both the MF and EBF configurations. Both the MF and the EBF configurations were found to be gust load critical because of low-wing-loadings. GLA was required and applied to both configurations.

Through the use of supercritical wing technology, it was possible to develop a wing for the MF configurations which was capable of a .8 Mach cruise speed. Since only 10 degrees sweep was required, maximum low speed lift was attained. The EBF configuration wing geometry was specified by NASA. The thickness distribution for the EBF configuration wing, which had a 30 degree sweep, was developed so it would have the same drag divergence Mach number as the MF configuration wing.

4.1 PROPULSION SYSTEM

The powerplants for this study were synthesized using the following ground rules and engine characteristics.

- Installation losses were assumed to be the same as those developed for installing a TF39-1A engine. The installation effects amount to four percent takeoff rated thrust loss and seven percent increase in SFC at cruise ($M = .8$ at 35,000 feet).
- Nacelle dimensions were scaled using the CF6-6D engine as the baseline (two-thirds length fan duct cowl).

$$\text{Fan Duct Diameter} = .0441 \sqrt{\left(F_N^*/F_{N_{\text{Ref}}}^*\right) \left(F_{N_{\text{Ref}}}^*\right)}, \text{ Ft.}$$

$$\text{Fan Duct Length} = 0.676 \sqrt{\left(F_N^*/F_{N_{\text{Ref}}}^*\right) \left(F_{N_{\text{Ref}}}^*\right)}, \text{ Ft.}$$

where

$$F_{N_{\text{Ref}}}^* = 39,400 \text{ lbs.}$$

- Basic acoustic characteristics were assumed to be equivalent to those of the CF6-6D engine.

- 1975 engine technology is a basic assumption of the study, therefore a two percent fuel flow improvement over installed TF39-1A performance at cruise was used. This amounts to a seven percent improvement over installed CF6-6D performance at cruise. Takeoff thrust lapse rate (thrust decay with velocity) was assumed to be the same as the lapse rate on the TF39-1A engine and is shown in Figure 1. TF39-1A lapse rate (F_N/F_{N^*}) is about two percent worse at takeoff speed than the CF6-6D. Installed thrust specific fuel consumption (TSFC) curves are shown in Figure 2.
- Weight scaling is commensurate with the GE-13/F6 engine.




Figure 1 Takeoff thrust lapse rate

4.2 WEIGHTS METHODOLOGY

The Airplane Sizing and Mission Performance (ASAMP) computer program (Reference 3) contains a Class I weight prediction subroutine. Class I weight predictions are developed parametrically based on preliminary configuration data. These methods were intended primarily for commercial subsonic transports; but have been expanded to cover STOL types, as discussed below. Class I weight prediction methods are expected to yield relative weight accuracies between 5% and 10% when comparing several aircraft designed to do similar transport tasks.

Emphasis has been placed on weight prediction improvements for MF and EBF STOL




Figure 2
Thrust specific fuel consumption

configurations. Since the Reference 1 study was completed, the weights module of the ASAMP computer program has been updated by the methods of Reference 4. The wing weight portion of this revision of the computer program has subsequently been updated by the methods of Reference 5. Adjustments to the methods of Reference 4, which is Conventional Takeoff and Landing (CTOL) oriented, to account for STOL weight trends are as follows:

| <u>Item</u> | <u>Weight Multipliers</u> |
|---|---------------------------|
| Fuselage | 1.15 |
| Landing Gear | 1.25 |
| Passenger Accommodations | .86 |
| Cargo Accommodations | .67 |
| Emergency Equipment | 1.12 |
| Air Conditioning | 1.05 |
| EBF Configurations Only (See Flow Chart, Figure 3). | |
| Trailing Edge Flap | |
| Area Factor | 1.47 |
| Fowler Motion Factor | 1.57 |




Figure 3 ASAMP wing weight flow chart

Weight multipliers are used in the following manner:

$$\left(\begin{array}{c} \text{ASAMP PREDICTED} \\ \text{COMPONENT WEIGHT} \end{array} \right)_{\text{STOL}} = \left(\begin{array}{c} \text{WEIGHT} \\ \text{MULTIPLIER} \end{array} \right) \left(\begin{array}{c} \text{ASAMP PREDICTED} \\ \text{COMPONENT WEIGHT} \end{array} \right)_{\text{CTOL}}$$

Background data and justification for the primary engine weight scaling factor are shown on Figure 4. The slope of the line through the data point labeled GE-13/F6 is .152 lbs/lbs. The scaling relationship for primary engine weight is:

$$\text{Primary Engine Weight} = .152 \left(F_{N^*}^* / F_{N_{\text{Ref}}}^* \right) \left(F_{N_{\text{Ref}}}^* \right), \text{ lbs.}$$

where:

$$F_{N_{\text{Ref}}}^* = 39,400 \text{ lbs.}$$

4.2.1 GUST LOAD ALLEVIATION SYSTEM WEIGHTS

An assumption of this study is that the airplane structure would be designed to 2.5 g's limit load factor. If the design load factor had to be increased due to gust loads, then a gust load alleviation (GLA) system would be incorporated, which would insure that the airframe would not be exposed to "g" loads higher than 2.5.

The systems involved in achieving GLA are:

Hydraulics and Pneumatics

Electronics

Surface Controls

Figure 5(a) illustrates the method for increasing the weight of these systems for design load factors higher than 2.5 due to gust load criticality.

The critical gust load factors are shown on Figure 5(b). The critical load factors for the wings of both the MF and EBF configurations occur at 360 KEAS (assumed V_{MO}) at 20,000 ft. in a 50 ft/sec (EAS) vertical gust. The two wings have a different gust load factor at the same wing loading because they have different wing planforms, and hence different lift curve slopes.

Figure 5(a) was derived from experience gained from the programs of References 1, 6, 7 and 8.

A more detailed weight investigation was made to check the validity of the hydraulic and pneumatic GLA weight multiplier shown in Figure 5(a). The 150 passenger 2,000 ft. MF configuration (lowest wing loading) was used for the investigation. At 360 KEAS four degrees of aft flap deflection is required to limit the airframe response to a 50 ft/sec vertical gust to 2.5 g's, (see Section 8.7.1). Total unbalanced surface hinge moments for this flight condition are shown in Table 1. The actuators would be housed inside the flap track fairings. The weight per unit force output compatible with 1970 actuator technology is .0023 lb/lb force for a 3000 psi hydraulic system. The resulting weights of the actuators required to deflect the GLA flap four degrees are also shown in Table 1.

An actuator rate requirement of 60 degree/sec will require the volumetric flow rates shown in Table 1. Based on current equipment, hydraulic pumps capable of supplying these flow rates will weigh






Figure 4 Dry engine weight



(a) Gust load alleviation
System weight penalties



(b) Design gust load factor
(Ref F.A.R. Part 25, Par. 25.341)

Figure 5 Gust load alleviation

approximately .8 lb/gpm flow rate. Hydraulic pump weights are also shown in Table 1. The last entry in Table 1 is the computed GLA weight multiplier which is derived from the combination of hydraulic pump and actuator weights. From Figure 5(a) the GLA weight multiplier used in this study is 1.36 for a wing loading of 42 psf.

TABLE 1 DETAILED GLA HYDRAULIC SYSTEM REQUIREMENTS

| No. Passengers | Moment (Ft-Lb) | Actuator Weight (Lb) | Hydraulic Flow Rate (gpm) | Hydraulic Pump Weight (Lb) | GLA Computed Weight Multiplier |
|----------------|----------------|----------------------|---------------------------|----------------------------|--------------------------------|
| 40 | 14,700 | 40 | 16 | 13 | 1.07 |
| 150 | 83,600 | 127 | 91 | 73 | 1.21 |
| 300 | 306,000 | 302 | 333 | 266 | 1.43 |

4.2.2 GROUP WEIGHT STATEMENT

Structures Group

The Structures Group is made up of the following items:

- Wing
- Horizontal Tail
- Vertical Tail
- Fuselage
- Landing Gear
- Engine Struts
- Engine Nacelles
- Engine Duct
- Engine Mount

Figure 6 is a correlation of actual versus ASAMP predicted wing weight for a wide range of airplanes using the method of Reference 5. A correlation of the total actual Structures Group weights compared to the ASAMP predicted summation is shown on Figure 7. The ± 10 percent accuracy lines are included.

Propulsion Group

The Propulsion Group contains the following items:

- Primary Engines
- Engine Accessories
- Engine Controls
- Engine Starting System
- Thrust Reversers
- Fuel System

Reference Figure 4 for primary engine weight. The total Propulsion Group weight correlation by ASAMP is shown on Figure 8.

Fixed Equipment Group

The Fixed Equipment Group contains the following items:

- Instruments
- Surface Controls
- Hydraulics
- Pneumatics
- Electricals
- Electronics
- Flight Desk Accommodations
- Passenger Accommodations
- Cargo Accommodation
- Emergency Equipment
- Air Conditioning
- Anti-Icing
- APU

The ASAMP predicted correlation with actual total Fixed Equipment is shown on Figure 9.

Standard And Operational Items

Standard Items

Standard items are equipment and fluids not an integral part of a particular aircraft and not a variation for the same type of aircraft. These items may include, but are not limited to the following:

- Unusable fuel and other unusable fluids
- Engine oil
- Toilet fluid and chemical
- Fire extinguishers, pyrotechnics, emergency oxygen equipment
- Structure in galley, buffet and bar
- Supplementary electronic equipment

Operational Items

Operational items are personnel, equipment and supplies necessary for a particular operation but not included in basic empty weight. These items may vary for a particular aircraft and may include, but are not limited to the following:

- Crew and baggage
- Manuals and navigational equipment
- Removable service equipment for cabin, galley and bar
- Food and beverages, including liquor
- Usable fluids other than those in useful load
- Life rafts, life vests and emergency transmitters
- Aircraft cargo handling system and cargo container

The correlation is shown on Figure 10.




Figure 6 Wing weight correlation




Figure 7 Structures group prediction accuracy




Figure 8 Propulsion group prediction accuracy




Figure 9 Fixed equipment group prediction accuracy




Figure 10 Standard and operational items prediction accuracy

4.2.3 FINAL WEIGHT STATEMENTS

Final weight statements for the 18 point design airplanes of this study are contained in Appendix A.

4.3 AERODYNAMICS

4.3.1 SUPERCRITICAL WING METHODOLOGY

The method used for this study enables the designer to choose the wing section required to satisfy a given design mission. The critical assumption is that the performance of a three-dimensional wing can be predicted from its two-dimensional section characteristics. Consequently, if the two-dimensional characteristics of a family of airfoil sections of current technology can be predicted, then a series of wings using these sections can be matched to the design mission and the optimum wing section selected. The problem to solve is: given the technology level and the three-dimensional drag divergence Mach number, how does one make the transformations to section drag divergence and lift and the corresponding section thickness ratio back out again to a wing thickness distribution that will in fact demonstrate the proper drag divergence and drag rise. A discussion of two-dimensional to three-dimensional correlation is required before this solution can be explained.


Two-Dimensional Generalization

Data from several two-dimensional wind tunnel tests have been generalized and used to predict the performance of a complete family of airfoil sections. Ordinarily the analysis is accomplished in two parts; first, polar shape is determined and second, drag rise and critical Mach number obtained. However, in this study the order of events in the use of this method was modified slightly. A cruise Mach number of .8 was a goal of the study. Based on previous experience the corresponding wing drag divergence Mach number was .81. Therefore, rather than solving for the drag divergence Mach number knowing thickness distribution, the reverse was done. Drag rise and polar shape are handled in ASAMP in the drag routine. This will be discussed in Paragraph 4.3.2

Drag Rise and Drag Divergence Mach Number

The key assumptions related to drag rise, drag divergence and the associated section thickness ratios are discussed below.

An idealized chordwise pressure distribution was devised as illustrated in the following sketch:



The upper surface c_p corresponds to a local Mach number of 1.2 (and extends from the leading edge) back to the pressure recovery point. At the recovery point (60 percent chord point) the c_p drops to a local Mach number of 1.0 with a linear recovery to the trailing edge. Assuming the thickness pressures from Reference 9, this c_p distribution will give various c_l capabilities as a function of free stream Mach number, thickness ratio and recovery point. An example of this process is shown on Figure 11 for a recovery point at .6 chord. This drag divergence Mach number curve represents the envelope of a family of airfoils designed to the above specified pressure distribution with different camber and thickness ratios. The level of technology represented by these data have been verified by personnel in the 8-Foot Tunnels Branch at NASA Langley.




Figure 11 Technology level

Two-Dimensional to Three-Dimensional Correlation

In order to use the generalized two-dimensional data, a procedure must be developed to convert the two-dimensional (2D) to three-dimensional (3D) characteristics. The obvious point of departure is simple sweep theory, which gives the following relationships:

$$M_{3D} = M_{2D} (\sec \Lambda)$$

$$C_L = c_l (\cos^2 \Lambda)$$

$$C_D = c_d (\cos^3 \Lambda)$$

This theory has been applied with two slight modifications. First, the sweep of the recovery point is used as the effective sweep angle when calculating the drag divergence boundary. This can be justified by noting it is the shock sweep that determines drag divergence, not the quarter chord sweep, and the shock is generally located at the section pressure recovery point. In addition, a .90 factor should be applied to the three-dimensional lift coefficient to allow for the decrease in lift at the root and tip. Therefore, the following expressions should be used for the three-dimensional drag rise derivation:

$$M_{3D_{DR}} = M_{2D} (\sec \Lambda_{EFF})$$

$$C_{L_{DR}} = .9 c_l (\cos^2 \Lambda_{EFF})$$

Second, a $\cos^2 \Lambda$ correction to the drag coefficient gives a much better correlation. It was found experimentally that the $\cos^3 \Lambda$ effect could not be justified. Consequently, the following expressions were used to calculate the three-dimensional polar shape:

$$C_{L_{PS}} = c_l (\cos^2 \Lambda_{c/4})$$

$$C_{D_{PS}} = c_d (\cos^2 \Lambda_{c/4})$$

Note the quarter chord sweep is recommended for use in the polar shape derivation because experimental results indicate that this relationship yields a valid correlation.

4.3.2 HIGH SPEED DRAG ESTIMATION

Prediction of subsonic airplane drag in the cruise configuration is an internal routine in ASAMP. The prediction methods are used when wind tunnel data is not available for the specific configuration of interest.

The drag estimation method used in this study is based on theoretical and experimental data which have been accumulated in recent years. Results from Boeing research programs and airplane development efforts, such as 737 and 747 are included.

The total subsonic drag is made up of three general terms:

$$C_D = C_{D_o} + C_{D_i} + \Delta C_{D_M}$$

| | | | |
|------------|----------|---------|-----------------------------|
| TOTAL DRAG | PARASITE | INDUCED | DRAG RISE (COMPRESSIBLE) |
|------------|----------|---------|-----------------------------|

Parasite Drag

Parasite drag includes the friction and pressure (separation, interference, profile) drag assuming no compressibility effects. All compressibility effects are accounted for in the ΔC_{D_M} term.

$$C_{D_o} = \frac{K_f}{S_{Ref}} \left[\sum (C_f A_{wet}) \begin{array}{l} \text{wing} \\ \text{horizontal tail} \\ \text{vertical tail} \\ \text{fuselage} \\ \text{nacelle} \end{array} \right]$$

where

K_f is an empirical factor for interference and construction tolerances representing C_{D_o}/C_{D_f} and is assumed to have the value of: $K_f = 1.26$

C_f is the friction drag coefficient for a fully turbulent boundary layer on a smooth flat plate corrected for temperature due to compressibility in the boundary layer by the mean enthalpy method. C_f is adjusted to account for friction drag increase due to overspeed. For this study C_f was assumed constant at a value of: $C_f = .0032$

Induced Drag

The major portion of the induced drag is caused by the wing lift. Several other airplane components can contribute also. The induced drag from these other components is included in the parasite drag. The drag method assumes that considerable tailoring and optimizing of the configuration has been accomplished. True elliptic loading is not anticipated due to the need for design compromise. The induced drag is estimated by the following equation:

$$C_{D_i} = \left[1.03 + \delta_o \left(\delta / \delta_o \right) + (D/b)^2 \right] \frac{C_L^2}{\pi AR}$$

$$\text{where: } \delta / \delta_o = \left(\frac{C_{L\delta}}{C_L} - 1 \right)^2$$

The constant (1.03) in the equation is a factor included to reflect a probable minimum nonellipticity. Further, nonelliptic effects may be eliminated for one specific C_L by proper spanwise camber and twist distribution. Minimizing the nonelliptic induced drag near the $C_{L_{design}}$ is usually a design goal. This design approach would provide slightly improved off design drag for holding or endurance performance, while trading trim drag improvements for increases in induced drag at the cruise condition.

The term $(\frac{D}{b})^2$ provides for an effect of the body on the wing load distribution and therefore on the induced drag.

The δ_o (δ/δ_o) term was derived from References 10 and 11 and provides for wing planform characteristics which dictate particular span load distributions. The basic planform effects can then be modified by some spanwise variation of camber and twist to achieve elliptic or nearly elliptic load distribution at one desired C_L .

Drag Rise

Drag rise includes all the additional drag occurring at Mach numbers greater than the incompressible Mach number. The drag rise includes the many drag increments from airplane components in the following equation:

$$\text{Total } \Delta C_{D_{M_{\text{Drag Rise}}}} = \Delta C_{D_{M_{\text{Wing}}}} + \Delta C_{D_{M_{\text{Body}}}} + \Delta C_{D_{M_{\text{Tail}}}} + \Delta C_{D_{M_{\text{Nacelle}}}} + \Delta C_{D_{M_{\text{Misc}}}}$$

The drag rise region occurs at Mach numbers greater than the incompressible Mach number. This is an arbitrary definition, since compressibility effects occur at all Mach numbers greater than zero. Any of the airplane components can contribute to the drag rise. However, the wing usually has the largest effect.

Wing

Determination of the wing drag rise characteristics are required first because other components are related to the wing (e.g., wing mounted nacelles, trim, wing mounted miscellaneous items, etc.). The first step of this procedure is to find the drag divergence Mach number (M_{DD}) for each of the selected C_L values. For this document, M_{DD} is defined as the Mach number at which the drag coefficient has increased by .0020 over the incompressible C_D . M_{DD} is determined by using the following equation:

$$M_{DD_{\text{WING}}} = M_{DD_c} + \Delta M_{\text{TECH}} + \Delta M_{\Lambda} + \Delta M_t$$

The M_{DD_c} term represents achievable values for a 30° sweep, 10% t/c, 1969 technology wing with various cambers and C_L . When the analysis involves other wing technology, the appropriate technology correction (ΔM_{TECH}) should be made. The ΔM_{TECH} correction for this study was derived from the data of Figure 11 and the methods of Section 4.3.1 for developing three-dimensional data from two-dimensional supercritical wind tunnel data.

After M_{DD} has been determined, the drag rise shape (ΔC_{D_M}) may be fitted through it. The drag rise shape is shown on Figure 12.

The effects of wing-body interference are an integral part of the wing data presented in this section. It is assumed that the configuration is well tailored. Untailored configurations can easily have a critical Mach number degradation of .02 or more.




Figure 12 Drag rise shape

Vertical and Horizontal Tails

The method just described for the wing is also used for the tail surfaces.

Body

The nose shape of the fuselages used for this study produce .0001 rise in drag due to compressibility at $M = .8$. The body drag rise equation is:

$$\Delta C_{D_{M_B}} = \frac{.7}{S} \sum (KB_I) \cdot (AP_I) (DL_I)^{5/3}$$

If $M \leq M_O$ then $KB_I = 0$. If $M_O < M < M_P$ then:

$$KB_I = \frac{1}{2} + \frac{\sin}{2} \left[\left(\frac{M - M_O}{M_P - M_O} \right) \pi - \frac{\pi}{2} \right]$$

M_O and M_P are determined from Figure 13.




Figure 13 Fuselage wave drag shape

Nacelles and Miscellaneous

Nacelle and other miscellaneous protuberance drag increases due to compressibility were accounted for in the interference conservatisms of the parasite drag buildup.

4.3.3 HIGH SPEED AERODYNAMIC CHARACTERISTICS

Final ASAMP predicted high speed drag polars are contained in Appendix B.

Flaps up aerodynamic characteristics of the MF configuration are shown on Figure 14. Lift curve slope and downwash data were estimated using the methods of Reference 12. Neutral point was estimated from Reference 13.

Flaps up aerodynamic data for the EBF configuration were developed from unpublished NASA wind tunnel data. A three-view of the EBF configuration wind tunnel model is shown in Figure 15.




Figure 14 Flaps up aerodynamic data for the MF configurations

WING:

Area, Sq. Ft. 5.202
 Mean aerodynamic chord, Ft. .885
 Span, Ft. 6.240
 Aspect ratio 7.48

HORIZONTAL TAIL:

Area, Sq. Ft. 1.551
 Mean aerodynamic chord, Ft. .699
 Span, Ft. 2.613
 Aspect ratio 4.40

VERTICAL TAIL:

Area, Sq. Ft. 1.488
 Mean aerodynamic chord, Ft. .964
 Span, Ft. 1.600




Figure 15 EBF configuration wind tunnel model

Page intentionally left blank

4.3.4 LOW SPEED AERODYNAMIC CHARACTERISTICS

Low speed drag polars were estimated for the MF configurations using the methods of Reference 14. The wing flap system is shown on Figure 16. The method assumes the following buildup of the untrimmed drag polar:

$$C_{D_{\text{FLAPS DOWN}}} = C_{D_{\text{P MIN CRUISE}}} + \frac{C_L^2}{\pi AR} + \Delta C_{D_{\text{P MIN LE}}} + \Delta C_{D_{\text{P MIN TE}}} + \Delta C_{D_{\text{i TE}}} + \delta C_{D_{\text{P}}} + \Delta C_{D_{\text{P}}}$$





Figure 16 Flap system - MF configuration

The low speed lift curves were also predicted by the methods of Reference 14, however, maximum lift values were improved by 5 percent to account for 1975 capabilities. Estimated drag values were used. Flaps down pitching moment characteristics were estimated by the methods of Reference 14. The MF configuration low speed aerodynamic characteristics, out of ground effect, are shown on Figure 17.


The low speed aerodynamic characteristics for the EBF configuration were obtained from unpublished NASA wind tunnel data. A three-view of the EBF configuration wind tunnel model is shown in Figure 15. Lateral, directional and engine out data were provided by NASA Langley in a preliminary, unchecked preworking paper. The wind tunnel model configuration chosen for use in this study is as follows:

| | | |
|---|---|-----|
| Bypass ratio | = | 6.2 |
| High horizontal tail location (T-tail) | | |
| Horizontal tail incidence angle | = | 5° |
| Leading edge slat chord (%C) | = | 25% |
| Leading edge slat deflection | = | 50° |
| Part span flaps | | |
| Engine out rolling moment trimmed with ailerons | | |

(a) Lift



(b) Pitching moment



Note: $W/S = 60 \text{ lbs/ft}^2$

(c) Drag




Figure 17 Estimated tail off low-speed aerodynamic characteristics - MF configuration

Wind tunnel data were taken for three flap settings; 0° , 35° and 65° , and three values of C_T : 0, 2 and 4. To facilitate the estimation of airplane performance from this data, cross plots were made which describe force polars for intermediate flap settings and C_T 's, i.e., 15° , 25° , 45° and $C_T = .5$ and 1.0.

5.0 TAKEOFF AND LANDING

Takeoff and landing performance was calculated using a computer program which has a ground effect subroutine. This subroutine calculates the changes in lift and drag over a specified range of ground heights. The method was used for both MF and EBF configurations.

5.1 TAKEOFF RULES AND PROCEDURE

Takeoff performance is calculated by numerical integration of the longitudinal and vertical equations of motion, based on inputs of aerodynamic, propulsion and geometric information for an airplane.

The takeoff calculation procedure is carried out within the bounds of specified margin and gradient criteria. These criteria are:

- $V_{LOF} \geq 1.05 V_{MU}$ O.E.I. $\left. \begin{array}{l} \text{(One Engine Inoperative)} \\ \text{If Airplane is Geometry Limited} \end{array} \right\}$
- $V_{LOF} \geq 1.08 V_{MU}$ A.E.O. $\left. \begin{array}{l} \text{(All Engines Operating)} \end{array} \right\}$
- $V_{LOF} \geq 1.1 V_{MC}$
- $V_R \geq 1.05 V_{MC}$
- $V_{2O.E.I.} \geq 1.2 V_S$
- 2nd segment climb gradient (one engine inoperative)
 - $\geq .030$ (4 engine airplane)
 - $\geq .027$ (3 engine airplane)
- $V_1 \leq V_R$

The minimum unstick speed is calculated according to Reference 15. An optimization routine allows the best flare profile to be calculated for minimum flare distance. A matrix of gradient and margin data for the configuration is generated automatically as a function of T/W and C_L for both the all engines operating and one engine inoperative conditions.

The takeoff calculation is initiated by the determination of V_{MU} . Using the maximum attitude (geometry limit) at lift-off, the minimum lift-off speed is computed. If insufficient gradient capability is available, the speed is increased systematically until either sufficient gradient is available, or the gradient capability fails to increase with increasing speed, in which case the calculation is terminated. This procedure is completed for all engines operating and one engine inoperative. Following the computation, an estimate of rotation speed is made based on a specified maximum pitch rate and acceleration. V_1 is then set equal to V_R , and the ground run, flare and stopping time histories are calculated by numerical integration of the equations of motion. The

relevant margins and gradient criteria at V_R , V_{LOF} and V_2 are then checked for both all engines operating and one engine inoperative. If any criteria is not satisfied, the rotation speed is increased systematically. After all criteria are satisfied, the optimum rotation speed to minimize the field length is determined, whether it be limited by all engine or engine out criteria. Following this optimization, the stopping distance is calculated. If the airplane is stopping distance limited, V_1 is reduced until the distance to continue takeoff with an engine out and the distance to stop with an engine out are within a specified tolerance.

Takeoff Input Data

Aerodynamic data are input in the form of a matrix of free air trimmed data versus angle of attack and C_T (for powered lift airplanes), for all engines operating and one engine inoperative. The data is repeated for up to five flap angles. The flap angle selected for takeoff need not correspond to one of those input, since the program interpolates between the data sets. The ground effect on lift and drag may be calculated by a subroutine in the program, or if desired, may be input for each takeoff flap angle in the form of a matrix of lift ratios and drag increments versus angle of attack, C_T and ground height. For conventional airplanes the reference C_T is set to zero and this specific dimension in both free air and ground effect matrices reduces to a one element array.

The propulsion data are input as three arrays of thrust component ratios versus speed. The three arrays are the blowing thrust on a powered lift airplane, (T_{BL}/T_{REF}) , the ram drag of the engine (D_{RAM}/T_{REF}) , and the direct thrust from the engine which does not interact with lift and drag (T_{PRIM}/T_{REF}) . The term T_{REF} is the reference engine size which corresponds to the selected (T_{REF}/W) for a particular case. For a conventional airplane the thrust is input the same way except (T_{BL}/T_{REF}) is set to zero.

Various geometric properties of the airplane are required such as M.A.C., gear stroke, and maximum pitch attitude at lift-off and during climbout.

Maneuver margin and climb gradient requirements at V_2 must be input for the takeoff calculation. The resulting takeoff speed schedule will attempt to satisfy these requirements by overspeeding if necessary.

Various constants for the calculation of refused takeoff (R.T.O.) stopping distance must be input. These consist of items such as braking coefficient, transition time, reverser effectiveness, etc.

Ground Run Calculation Method

For conventional airplanes where lift and drag are not strong functions of engine thrust, the ground run calculation is a simple integration of the acceleration from zero speed to V_R . The terms accounted for in the equation of motion are fan thrust, primary thrust, ram drag, aerodynamic drag, and ground roll friction based on gear reaction. The calculation is made for all engines operating up to V_R , then for all engines operating up to V_1 followed by one engine out up to V_R .

The calculation becomes somewhat more complex for a powered lift airplane since both lift and drag are expressed as functions of C_T . At low speeds this quantity becomes very large and exceeds the maximum value for which aerodynamic data is input. It is therefore necessary to change the calculation procedure below a speed corresponding to $C_{T\text{MAX}}$. The method used is to interpolate linearly between a specified static acceleration computed using $\left(\frac{T_{\text{STATIC}}}{T_{\text{REF}}}\right)$ and $\left(\frac{T_{\text{PRIM}}}{T_{\text{REF}}}\right)$, and the acceleration at $C_{T\text{MAX}}$. Clearly, the error in the procedure is minimized if $C_{T\text{MAX}}$ is large. In practice the sensitivity of the ground run distance to $\left(\frac{T_{\text{STATIC}}}{T_{\text{REF}}}\right)$ is quite low since the effect of acceleration changes over the first part of the ground run is also low.

Stopping Distance Calculation

The stopping calculation consists of two segments,

- The transition segment from a condition with all engines operating to a condition with reverse thrust, brakes on and spoilers up, and
- The stopping segment from the end of transition to full stop.

The deceleration during transition is based on a linear interpolation between the two end points. The values of lift and drag at the end of transition are evaluated at $C_T = 0$ for a powered lift airplane. These values are then used during the stopping segment. If thrust reversers are used, the reverser effectiveness and number of engines used are applied directly to the specified reference thrust-to-weight ratio to calculate the reverser retarding force, regardless of whether the airplane is conventional or of the powered lift type.

Flare Calculation Method

The flare calculation is basically the integration of the longitudinal and vertical equations of motion for a specified input pitch time history from the point of rotation to the clearance of a 35 foot obstacle. The gear representation is simple, consisting of a linear spring with specified stroke from taxi position, and specified preload at maximum extension. The point of lift-off occurs when the gear load becomes zero or equal to the preload.

Although the initial pitch history is specified, the computational routine has four optional features that essentially eliminate the sensitivity of the takeoff calculation to these specifications. These options are:

- A load factor limitation that enables the user to specify n_{max} during the flare; this value will not be exceeded.
- A velocity feedback system that either prevents the airplane from losing any significant amount of speed or allows a specified speed loss between lift-off and V_2 . This is

accomplished by automatic modification of the pitch profile when low longitudinal accelerations are registered. The procedure is designed to simulate typical pilot reactions observed from flight testing, and appears to work quite well.

- The input pitch profile is used directly for the all engines operating flare calculation, however, for the engine out flare, a reduction factor may be input that results in a proportionate reduction in attitude versus time, i.e., $\theta_{OEI} = (1-THK) \theta_{AEO}$ where THK is an empirical factor. Typical flight test data shows a conservatism on the part of the pilot when he encounters an engine failure condition. This generally results in a pitch rate reduction of 20 percent to 30 percent which may be simulated by the appropriate choice of THK.
- An optimizing routine is available that will generate the flare procedure that minimizes the flare distance within the constraints of a maximum pitch rate, acceleration, lift-off attitude and attitude at 35 feet.

Ground Effect Calculation

The program user has the option of either specifying the ground effect on lift and drag, or he may elect to use the ground effect subroutine. This routine calculates the changes in lift and drag over a specified range of ground heights. The theory is applicable to either conventional or powered lift airplanes.

The takeoff program was used on the 737-200 airplane to obtain comparison with flight test results. The agreement is quite close both in terms of general level and also variation in flare technique.

5.2 LANDING RULES AND PROCEDURE

Landing approach speeds are calculated using the following set of rules:

Sea Level, Standard Day

Dry Runway

35 Ft. Obstacle

1.10 Flare Load Factor

3 Ft/Sec. Touchdown Sink Rate

6° Glide Slope


.6 Field Length Safety Factor

1.0 Sec. Coast Time

.35 g Deceleration

The sensitivity to variations in flare load factor and coast time in terms of F.A.R. field length and approach speed is shown on Figure 18.

(a) Effect of flare load factor



Sea level, standard day

Obstacle = 35 feet

Ground roll deceleration = $0.35g$

F.A.R. field length factor = 0.6

$\gamma = -6^\circ$

$(R/S)_{\text{Touchdown}} = 3 \text{ ft/sec}$

(b) Effect of coast time




Figure 18 Landing rules sensitivity

The MF configuration landing approach speed margin is $1.3 V_S$. The EBF configuration landing approach margins and go-around procedures are discussed in the following paragraphs.

EBF configuration gradient and margin rules are listed in Table 2. Since wind tunnel data were used in the computer program, the lift margin rules are equivalent to a $1.3 V_S$ safety margin. In other words it is assumed that:

$$\left[\left(\frac{C_{LV_{MIN}}}{C_{L_{APP}}} - 1 \right) \geq .44 \right]_{\text{Wind Tunnel}} = \left[\left(\frac{C_{LV_{MIN}}}{C_{L_{APP}}} - 1 \right) \geq .69 \right]_{\text{Full Scale F.A.R.}}$$

TABLE 2 LANDING GRADIENT AND MARGIN RULES

| Rule | Flap Setting | Flight Phase | Velocity | Power Setting | No. of Eng. Operating | Conditions to be met |
|------|--------------|----------------------------|-----------|---------------|-----------------------|---|
| 1 | Approach | Landing (Gear down) | V_{APP} | Approach | All | $[\alpha_s - \alpha_{APP}] \geq 15^\circ$ |
| 2 | Approach | Landing (Gear down) | V_{APP} | Approach | One out | $[\alpha_s - \alpha_{APP}] \geq 10^\circ$ |
| 3 | Approach | Balked landing (Gear down) | V_{APP} | Max | All | $[(C_{L_S}/C_{L_{APP}}) - 1] \geq .44^*$ Gradient $\geq .032$ |
| 4 | Approach | Balked landing (Gear down) | V_{APP} | Max | One out | $[(C_{L_S}/C_{L_{APP}}) - 1] \geq .30^*$ $\gamma \geq 0^\circ$ |
| 5 | Go-around | Balked landing (Gear up) | V_{APP} | Max | One out | $[(C_{L_S}/C_{L_{APP}}) - 1] \geq .25^*$ or $[\alpha_s - \alpha_{APP}] \geq 10^\circ$ Gradient $\geq .027$ |

*Based on wind tunnel data

This represents a 17 percent improvement in maximum lift capability from "1g" wind tunnel to flight test F.A.R. stall. The 17 percent is made up of an assumed seven percent improvement in "1g" stall $C_{L_{max}}$ wind tunnel to "1g" $C_{L_{max}}$ flight test and 10 percent improvement from "1g" flight test to F.A.R. stall. This reasoning also applies to the listed engine out "g" margins. The gradient rules are from Reference 16. As an additional check for safety, $\Delta\alpha$ margins are monitored in the gradient and margin computer program. The $\Delta\alpha$ margins (Rules 1 and 2) of Table 2 are intended to provide vertical gust protection equivalent to current commercial transports.

Reference 17 contains calibration information for the propulsion system simulators used on the EBF configuration wind tunnel model. Calibration results indicate that the secondary weight flow

induced through the ejector inlet by the primary nozzles is only about one-half as high as a full scale engine with the same bypass ratio at a typical STOL takeoff airspeed. This means that the wind tunnel data contains only one-half the ram drag. Therefore, one-half the TF39-1A ram drag was added to account for this.

The gradient and margin computer program calculates the maximum allowable C_L 's and the required approach T/W's to meet specified "g" margins from stall and climb gradient requirements, respectively. The allowable approach C_L is computed for the range of T/W's used in the margin and gradient calculation. For a conventional airplane these numbers would not be a function of T/W. The required approach T/W's are computed at C_L 's used in the margin and gradient calculation.

The procedure for determining the approach speed and required T/W for each approach flap setting considered is shown on Figure 19. The limiting approach C_L is described by the most critical angle of attack margin ($\Delta\alpha$) or acceleration margin (Δg) between an approach flight path angle and a go-around climb gradient for all engines or engine out, at the approach flap setting (Rules 1, 3, 2 or 4, respectively, in Table 2). If the all engine condition is critical (which has been the case for all EBF configuration flap settings considered in this study), then the C_L which corresponds to the most critical margin between $\Delta\alpha$ and Δg (Rule 1 or 3) is the limiting approach C_L . For the EBF configuration the $\Delta\alpha = 15^\circ$ requirement at approach power setting (Rule 1) has consistently been more critical than $\Delta g = .44$ at maximum thrust, therefore, it has defined the approach speed.

The design thrust to weight ratio (T/W) could be defined by the greater of:

- | | | | |
|-------------|---|---------------------|--------------------------|
| 1) gradient | = | .032 all engine | } approach flap setting |
| 2) gradient | = | 0 one engine out | |
| 3) gradient | = | .027 one engine out | |
| 4) gradient | = | .027 one engine out | } go-around flap setting |

at the limiting C_L defined above (shown as points A, B, C and D, respectively, on Figure 19). The design T/W is always critical for Condition 2 or 4.

During the initial phase of the study Rule 4 from Table 2 contained a requirement to meet Condition 3 from above. For the EBF configuration being studied the T/W required to climb with a gradient of .027, engine out, at the approach flap setting would always be critical. With this in mind, the decision was made to allow a configuration change to a lower flap setting in the event that an engine out go-around is necessary. This procedure resulted in Condition 2 from above being critical for assumed approach flap settings above 30 degrees. For assumed approach flap settings less than 30 degrees, Condition 4 was critical.

The calculations are made for various flap angles and wing loadings. The results identify the optimum flap angles and corresponding minimum operating speeds for a specified configuration.

The development of actual EBF configuration wing loadings and design T/W's are contained in Appendix C.




Figure 19 Powered lift approach analysis procedure

6.0 VERTICAL TAIL SIZING

Vertical tail sizes were determined considering:

- (1) Ground minimum control speed requirement, (V_{MCG})
- (2) Static and dynamic directional stability requirements
- (3) Crosswind landing requirement

Figure 20 schematically illustrates the vertical tail area requirements as a function of the critical engine moment arm. For multi-engine aircraft with wing-mounted engines, the minimum critical engine moment arm is usually limited by providing adequate clearance between engines or between engine and fuselage to minimize interference effects which would penalize cruise performance. The maximum allowable vertical tail area is dictated by the crosswind requirement. A small vertical tail usually improves the crosswind landing capability because of the directionally unstable wing-body combination which provides a favorable yawing moment. The minimum vertical tail size is determined from the ground minimum control speed requirement and/or static and dynamic stability requirements.




Figure 20 Vertical tail sizing

Ground Minimum Control Speed Requirement

During the takeoff run it must be possible to maintain control of the aircraft following a sudden loss of thrust on the most critical engine. If the critical engine fails prior to reaching the ground

minimum control speed (V_{MCG}), the takeoff must be aborted. If the critical engine fails at or above V_{MCG} , the aircraft must have adequate aerodynamic control power to continue the ground roll with takeoff thrust on the remaining engines. A maximum deviation of 25 feet from the intended ground roll path is allowed following an engine failure. No credit is allowed for nose wheel steering.

Sizing the vertical tail to allow a 25 foot deviation from the runway centerline allows the most critical engine to fail prior to a speed at which the rudder controls can statically balance the engine out yawing moment. If the takeoff run is continued following an engine failure, the speed continues to increase as the aircraft departs from its originally intended flight path. Prior to reaching the maximum allowed 25 foot deviation from the intended ground path, the speed has increased and at this speed the rudder control must be able to overcome the engine out yawing moment. The aircraft is then able to return to its originally intended flight path without exceeding the 25 foot allowed deviation. This vertical tail sizing method (besides being cumbersome to solve because the airplane dynamics are involved) gives a V_{MCG} which is less than a static analysis in which the rudder yaw moment exactly balances the engine out yaw moment.

For this study the vertical tail area required to satisfy the ground minimum control speed requirement was determined from a static balance of engine out yaw moment and rudder yaw moment at the takeoff decision speed V_1 . The V_1 speed is the maximum allowable V_{MCG} speed.

The ratio of vertical tail area to wing area required to statically balance the engine out yaw moment using only rudder control is given by:

$$\frac{S_V}{S} = \frac{295 \left(\frac{T}{NW} \right) \left(\frac{Y_e}{l_v} \right) \frac{W}{S}}{C_{LV} V_1^2}$$

Because of the low speeds at which STOL aircraft operate, the critical engine moment arm must be kept small if reasonable sized vertical tails with conventional aerodynamic controls are used.

Also of importance is the amount of usable vertical tail lift coefficient which can be generated by the rudder. The lift coefficient is determined primarily by the size of the rudder and the complexity of the rudder or a high lift system, i.e., simple flap control, double articulated flap control, blown surface, etc.

Static and Dynamic Directional Stability Requirements

The static directional stability derivative $C_{n\beta}$ (weathercock stability) does not have an explicit required value; however, when the aircraft is in a sideslip relative to its flight path, the yawing moment produced must tend to restore the aircraft to symmetric flight. In terms of rudder required to sideslip the aircraft, right rudder pedal deflection and force must produce left sideslip and left rudder pedal deflection and force must produce right sideslip.

The total airplane weathercock stability is composed of the wing-body contribution (usually unstable) and the vertical tail contribution (stable) or

$$C_{n\beta} = C_{n\beta_{WB}} + C_{n\beta_V}$$

The wing-body contribution ($C_{n\beta_{WB}}$) is primarily a function of the body volume coefficient $\frac{S_B l_B}{S b}$ and was estimated using data from the Boeing family of airplanes.

The vertical tail contribution ($C_{n\beta_V}$) is estimated by

$$C_{n\beta_V} = a_V \left(\frac{S_V}{S} \right) \left(\frac{l_V}{b} \right) \left(1 - \frac{d\sigma}{d\beta} \right)$$

The sidewash factor is difficult to estimate and wind tunnel tests are required to determine the value. In general, sidewash factors are favorable and tend to increase the level of directional stability above the value predicted if the effect is neglected.

For this study the sidewash factor was neglected, therefore, the static directional stability level should be conservative.

The complete three degree-of-freedom equations for determining the dynamic stability are complicated for the basic airframe and more complex when an automatic damping system is added. In order to determine the vertical tail area required to provide the aircraft with satisfactory dynamic stability characteristics (reasonable restoring accelerations) in this preliminary design study, a simplified approach was used. The Dutch roll natural frequency can be approximated by

$$\omega_{n_{DR}}^2 = \frac{C_{n\beta} q S b}{I_{zz}}$$

If more than one aircraft is being studied or evaluated, all aircraft can be designed to have the same basic Dutch roll natural frequency if:

$$\frac{C_{n\beta_x}}{C_{n\beta_o}} = \left(\frac{I_{zz_x}}{I_{zz_o}} \right) \left(\frac{S_o}{S_x} \right) \left(\frac{b_o}{b_x} \right) \left(\frac{V_{e_o}}{V_{e_x}} \right)^2$$

The subscript "o" indicates the values of a baseline aircraft and the subscript "x" indicates the values of any other aircraft. The weathercock stability derivative $C_{n\beta}$ is a function of S_V/S .

Therefore, the vertical tail area to wing area ratio $(S_V/S)_x$ required to give the aircraft in question the same Dutch roll natural frequency (same restoring acceleration due to sideslip) as the baseline aircraft can be determined.

The baseline aircraft used for this study was the 3,500 foot field length, 150 passenger aircraft, since it is a more conventional type aircraft. An estimate of the Dutch roll natural frequency at the maximum gross weight and lift-off speed gives $\omega_{n_{DR}} = .37$ rad/sec with $C_{n\beta} = .001/\text{deg}$. The

Reference 19 STOL study required ω_{nDR} to be $\geq .4$ rad/sec. A study comparing the validity of the approximation to the Dutch roll natural frequency was made (Reference 20) and showed that for small values of ω_{nDR} the approximate solution could be anywhere from 12 percent to 25 percent below the exact solution. It is anticipated that $C_{n\beta} = .001/\text{deg}$ for the 3,500 foot field length aircraft will exceed the minimum Dutch roll natural frequency requirement of .4 rad/sec as specified in Reference 19.

Crosswind Landing Requirement

A requirement of this study was that the airplane must have sufficient directional control power to hold a constant ground track in a 25 knot 90 degree crosswind at the approach speed. If the yaw moment due to lateral control required to balance the roll moment is assumed to be zero, the rudder generated lift coefficient on the vertical tail required to exactly balance the weathercock yaw moment ($C_{n\beta} \beta_{\text{cross wind}}$) can be expressed as:


$$C_{LV} = \frac{\left[C_{n\beta}^{\text{wing body}} + a_V \frac{S_V \ell_V}{S b} \right] \left[\sin^{-1} \left(\frac{V_{cw}}{V_e} \right) - \delta_{\text{crab}} \right]}{\frac{S_V \ell_V}{S b}}$$

The procedure used in checking the crosswind landing capability was to use the vertical tail to wing area ratio (S_V/S) required to provide the aircraft with adequate engine out directional control and/or directional stability and see if the resulting tail lift coefficient required for crosswind landing is less than that required for engine out control.

The rudder directional control required for crosswind landing is significantly influenced by the type of lateral control used on the aircraft. Aircraft with large amounts of dihedral effect (negative $C_{l\beta}$) using spoiler lateral control devices require larger amounts of rudder control than aircraft with aileron controls. The drag associated with spoiler control requirements in a crosswind landing is in opposition to the aircraft yaw moment produced by the rudder. The vertical tail lift coefficient requirement for engine out control was compared to that required for the crosswind landing.

6.1 MECHANICAL FLAP CONFIGURATION VERTICAL TAIL SIZE

A trade study of the vertical tail area to wing area ratio for the 150 passenger aircraft was made as a function of the field length requirements for various levels of vertical tail lift coefficient (ground minimum control speed requirement) and weathercock stability (dynamic stability requirement). The data are shown in Figure 21. The vertical tail has been sized for dynamic stability. The amount of rudder generated vertical tail lift coefficient for the engine out control requirement with the vertical tail sized for dynamic stability is less than the design limit ($C_{LV} \leq 1.0$).



Note: Nominal vertical
tail arm $\ell_v = 660$ in.

--- Engine out control
 $\sim V_{MCG}$


— Weathercock stability

- - - Dynamic stability

⊕ Required tail area ratio
for nominal tail arm

Figure 21 MF configuration vertical tail sizing

Figure 22 shows the vertical tail lift coefficient which must be generated by the rudder to meet the engine out requirement or the 25 knot crosswind requirement. The engine out requirement is critical. The vertical tail lift coefficient required for the 25 knot crosswind capability (no lateral control yaw moment) is significantly less than the engine out requirement. Rudder authority is expected to be adequate for the crosswind landing with a spoiler type lateral control system used in conjunction with an aileron located in the "cut out" region behind the wing mounted nacelles. A summary of the vertical tail size requirements as a function of the field length for the 150 passenger airplane is shown in Table 3. A nominal vertical tail arm of 660 inches was assumed.



Notes:

C_{L_V} ~ vertical tail lift coefficient which must be generated by the rudder

Nominal vertical tail arm $l_v = 660$ in.

Vertical tail sized for dynamic stability


Figure 22 MF configuration crosswind capability

The nominal tail arm used for the vertical tail sizing trade study (Figure 21) required adjustments for weight and balance considerations and scaling for the 40 and 300 passenger aircraft. Figure 23 shows the influence of changing the tail arm parameter $\frac{l_v}{b/2}$ on the vertical tail area ratio (S_V/S) for the stability critical mechanical flap configuration. Figure 23 was used to finalize the tail size for the 150 passenger aircraft and to size the vertical tails for the 40 and 300 passenger aircraft.

TABLE 3
NOMINAL VERTICAL TAIL SIZE, 150 PASSENGER, MF CONFIGURATION

| Field Length Feet | 2000 | 2500 | 3500 |
|---|------|------|------|
| Vertical tail area ratio S_V/S | .136 | .133 | .158 |
| Usable lift coefficient which must be generated by the rudder | .925 | .79 | .595 |

MF Configuration



Note: Dashed lines represent basic 150 passenger airplane with nominal vertical tail arm 660 in.

Figure 23. Effect of vertical tail arm parameter $\frac{l_v}{b/2}$ on vertical tail size (S_V/S)

6.2 EXTERNALLY BLOWN FLAP CONFIGURATION VERTICAL TAIL SIZE

Figure 24 shows results of a trade study of the vertical tail area to wing area ratio for the 150 passenger aircraft. Vertical tail lift coefficient (ground minimum control speed requirement), weathercock stability and dynamic stability requirements were considered.

Two takeoff thrust-to-weight ratios were considered:


- Design thrust-to-weight
- Reduced thrust-to-weight to match takeoff field length requirements

The EBF configuration thrust required is critical for engine out go-around. If this design thrust is used for takeoff the resulting field length is less than the design field length. An excessive vertical tail size is required for engine out control on the 2,000 ft. and 2,500 ft. field length aircraft. The vertical tail area to wing area ratios for the 2,000 ft. and 2,500 ft. field length aircraft are .361 and .225 respectively for a usable vertical tail lift coefficient of 1.0. As a result, a partial power takeoff was considered with a thrust-to-weight ratio which would produce a field length equal to the design field length. The vertical tail size requirements for the 2,000 ft. and 2,500 ft. field length aircraft were significantly reduced (vertical tail area to wing area ratios of .222 and .158 respectively). The 3,500 ft. field length aircraft is stability critical for either thrust-to-weight ratio considered.

Figure 25 shows the vertical tail lift coefficient which must be generated by the rudder to meet the engine out requirement or the 25 knot crosswind requirement. These data assume the vertical tail has been sized for the reduced thrust takeoff. As for the MF configuration, the vertical tail lift coefficient required for the EBF configuration in a 25 knot crosswind (no lateral control yaw moment) is much less than the engine out requirement. Rudder authority is expected to be adequate for the crosswind landing with a spoiler type lateral control system used in conjunction with an aileron located outboard of the outer flap section. A summary of the vertical tail size requirements as a function of the field length for the 150 passenger airplane (nominal tail arm of 660 in.) is shown in Table 4.

TABLE 4
NOMINAL VERTICAL TAIL SIZE, 150 PASSENGER, EBF CONFIGURATION

| Field length | 2,000 | 2,500 | 3,500 |
|---|--------------------|-------|--------------------|
| Vertical tail area ratio S_V/S | .222 | .158 | .162 |
| Usable lift coefficient which must be generated by the rudder | 1.0 | 1.0 | .732 |
| | V_{MCG} Critical | | Stability Critical |



Note: Nominal vertical tail arm $\ell_v = 660$ in.

———— Engine out control $\sim V_{MCG}$, max design T/W

———— Weathercock stability

- - - - Dynamic stability

----- Engine out control $\sim V_{MCG}$, design T/W reduced for design field length


⊕ Required tail area ratio for nominal tail arm

Figure 24 EBF configuration vertical tail sizing

150 passengers

Vertical tail sized for:

Engine out  Dynamic stability




C_{L_V} ~ Vertical tail lift coefficient which must be generated by the rudder

Nominal vertical tail arm $l_V = 660$ in.

Figure 25 EBF configuration crosswind capability

The nominal tail arm ($l_V = 660$ in.) used for the vertical tail sizing trade study (Figure 24) required adjustments for weight and balance considerations and for the 40 and 300 passenger aircraft. Figure 26 shows the influence of changing the tail arm parameter $\frac{l_V}{b/2}$ on the vertical tail area ratio S_V/S for the engine out critical and stability critical EBF configurations. Figure 26 was used to finalize the tail size for the 150 passenger aircraft and to size the vertical tails for the 40 and 300 passenger aircraft.

EBF Configuration



Note: Dashed lines represent basic 150 passenger airplane with nominal vertical tail arm 660 in.

Figure 26 Effect of vertical tail arm parameter $(\frac{l_v}{b/2})$ on vertical tail size $(\frac{S_v}{S})$

Page intentionally left blank

7.0 HORIZONTAL TAIL SIZING

Horizontal tail sizes were determined by:

1. Sufficient static longitudinal stability.
2. Adequate nose wheel steering.
3. The ability to rotate the aircraft to takeoff attitude at the rotation speed.
4. The ability to trim the aircraft at the approach speed.
5. Usable CG range which encompasses the variations in CG which occur due to fuel usage or passenger loading.

Items 1 or 2 determine the aft CG limit while Items 3 or 4 determine the forward CG limit. Item 5 is the difference in the forward and aft CG limits as determined by the critical Items 1 through 4. Figure 27 schematically illustrates the horizontal tail area requirements as a function of CG position. The optimum tail area for a required CG range is achieved by varying the wing position until a location is found in which the forward and aft aerodynamic CG limits just encompass the forward and aft weight and balance loading limits.




Figure 27 Horizontal tail sizing schematic

Static Longitudinal Stability

The static longitudinal stability criteria chosen for this study was to provide the aircraft with a three percent static stability margin when flying with the CG on the aft limit. The horizontal tail area to wing area ratio (S_H/S) required to provide the aircraft with neutral static stability ($dC_m/dC_L = 0$) was computed by:

$$\frac{S_H}{S} = \frac{\left(\frac{x_{CG}}{\bar{c}} - \frac{x_{AC_{WB}}}{\bar{c}} \right)}{\frac{a_H}{a_{WB}} \left(1 - \frac{d\epsilon}{d\alpha} \right) \left(\frac{l_H}{\bar{c}} + .25 - \frac{x_{CG}}{\bar{c}} \right)}$$

The horizontal tail area to wing area ratio required for a three percent static margin is then obtained by limiting the CG position three percent ahead of the values used in the equation above.

Nose Wheel Steering

When the aft CG limit as a function of the horizontal tail area to wing area ratio has been determined which will satisfy the static longitudinal requirements, the nose wheel steering requirement can be satisfied by proper placement of the main landing gear. With the CG at the aft limit for the static stability requirement, the main landing gear can be located so that adequate nose wheel steering is available for the aircraft considering power on and off effects. If the effective thrust line is located below the CG, nose wheel lightening can occur at low gross weights and high thrust applications. This type of design requires a larger margin between the aft CG and the main landing gear than a design with the thrust line located above the CG.

Using this technique forces the aft CG limit to simultaneously satisfy the static longitudinal stability requirement and the nose wheel steering requirement. The main landing gear were placed so the loading on the nose wheel was always greater or equal to five percent of the total zero velocity gear load. This is comparable to the gear load distribution on Boeing commercial aircraft. The horizontal tail area which will satisfy forward CG limit criteria can now be determined.

Nose Wheel Lift Off Requirement

When the rotation speed is reached during the takeoff ground roll it must be possible to rotate the aircraft to takeoff attitude at the most forward CG location and with the takeoff power setting. The horizontal tail area to wing area ratio (S_H/S) required to rotate the aircraft about the main gear was determined as follows:

$$\frac{S_H}{S} = \frac{\left(\frac{W/S}{q} - C_{L_{WB}} \right) \left(\frac{x_{MG}}{\bar{c}} - \frac{x_{CG}}{\bar{c}} \right) + C_{L_{WB}} \left(\frac{x_{AC_{WB}}}{\bar{c}} - \frac{x_{CG}}{\bar{c}} \right) - C_{m_{0WB}} - \frac{1}{q} \left(\frac{T}{W} \right) \left(\frac{W}{S} \right) \frac{z_T}{\bar{c}}}{C_{L_H} \left(\frac{x_{MG}}{\bar{c}} - \frac{l_H}{\bar{c}} - .25 \right)}$$

Trim at the Approach Speed

At the landing approach speed and in the landing configuration it must be possible to trim the aircraft with the stabilizer only (no elevator control). The horizontal tail area to wing area ratio required to trim the landing approach was determined by the following equation:

$$\frac{S_H}{S} = \frac{C_{m_{0WB}} + \frac{W}{qS} (X_{CG} - X_{AC_{WB}})}{C_{L_H} \left(\frac{l_H}{\bar{c}} + .25 - X_{AC_{WB}} \right)}$$

7.1 MECHANICAL FLAP CONFIGURATION HORIZONTAL TAIL SIZE

Horizontal tail sizing for the 150 passenger 2,500 foot field length airplane is shown in Figure 28. The CG travel from the aircraft fully loaded to empty varies from 32 percent MAC to 36.5 percent MAC respectively. The weight and balance analyses are shown in Appendix D. A 10 percent allowable CG range which will encompass the 4.5 percent CG variation requires a nominal horizontal tail to wing area ratio of .222. The aft CG limit (39 percent MAC) is high altitude cruise stability critical. The forward CG limit (29 percent MAC) is takeoff rotation critical. For the





Figure 28 MF configuration horizontal tail sizing

takeoff rotation a usable horizontal tail lift coefficient of - 1.0 is required. This level of lift coefficient is easily obtainable with stabilizer trim plus full deflection of a conventional elevator control surface. The approach trim condition is not critical in determining the forward CG aerodynamic limit.

The nominal horizontal tail arm ($l_H = 840$ in.) used for the horizontal tail sizing of the 150 passenger, 2,500 foot field length aircraft required adjustments for the 2,000 foot and 3,500 foot field length versions and required scaling for the 40 and 300 passenger versions.

Figure 29 shows the influence of changing the tail arm parameter ($\frac{l_H}{\bar{c}}$) on the horizontal tail area ratio (S_H/S). Figure 29 was used to adjust the tail sizing for the 150 passenger, 2,000 foot and 3,500 foot field length versions and to size the horizontal tails for the 40 and 300 passenger versions.



Note: Dashed line represents basic 150 passenger, 2,500 ft field length airplane tail size with nominal horizontal tail arm 840 in.

Figure 29 Effect of horizontal tail arm parameter ($\frac{l_H}{\bar{c}}$) on horizontal tail size (S_H/S)

7.2 EXTERNALLY BLOWN FLAP CONFIGURATION HORIZONTAL TAIL SIZE

Horizontal tail sizing for the EBF configuration involves solution of a unique problem not

encountered in the conventional MF configuration design, that of extreme wing placement. If the EBF configuration wing is longitudinally placed in a mid-fuselage position similar to CTOL wing-mounted engine configuration, the EBF configuration will have a forward CG problem due to the relatively large engines. This problem is schematically shown in the horizontal tail sizing diagram in Figure 30. The extreme forward CG location requires an excessively large horizontal tail to meet the forward CG requirements (for this particular design, takeoff rotation). For the required CG range, the aircraft now has an excessive static stability margin as shown in Figure 30. Several methods or combinations of methods are available to solve the problem:

- Increasing the amount of horizontal tail lift coefficient which can be generated by the elevator
- Adding ballast in the aft fuselage
- Moving the wing forward

The required horizontal tail area to rotate the aircraft to takeoff attitude is inversely proportional to the amount of negative horizontal tail lift coefficient which can be generated by the elevator. For the EBF configuration a usable horizontal tail lift coefficient (C_{L_H}) of -1.5 was assumed ($C_{L_H} = -1$ for the MF configuration). This effect on the horizontal tail size required for nose wheel lift off is also schematically illustrated in Figure 30. To achieve a usable horizontal tail lift coefficient of 1.5 requires a more sophisticated elevator design than would be required for the MF configuration.




Figure 30 Schematic EBF configuration horizontal tail sizing

By adding the proper amount of ballast in the aft fuselage the EBF configuration with a longitudinal wing location similar to CTOL aircraft can be balanced. An optimum size tail can be selected which will allow the aerodynamic limit to coincide with the structural weight and balance limits as illustrated in Figure 30.

The wing placement technique was used in lieu of the ballast technique to balance the aircraft and obtain an optimum size tail. This method makes use of the existing structure behind the wing for ballast without having to add any "dead weight" ballast.

Increasing the horizontal tail usable lift coefficient from -1 to -1.5 , and moving the wing to the most forward position relative to the fuselage without compromising good ground loading characteristics, allowed selection of an optimum size horizontal tail.

Figure 31 shows the EBF configuration horizontal tail sizing as a function of CG location for the wing located in a relative longitudinal position to the fuselage as the wind tunnel model, Figure 15. Figure 31 was constructed with a variable main landing gear position relative to the aft CG limit to maintain a constant percent of the total gross weight on the nose wheel for good nose wheel steering characteristics. For horizontal tail to wing area ratios between .199 and .246 a CG range varying from 0 percent to 10 percent becomes available which is based on a three percent static margin for the aft limit and takeoff rotation for the forward limit. The maximum required CG range was chosen to be 10 percent MAC. For horizontal tail area to wing area ratios greater than .246 the




Figure 31 EBF configuration horizontal tail sizing ~ wing location of Figure 15

available CG range will exceed 10 percent if the same critical conditions (three percent static margin and takeoff rotation) are used to define the forward and aft CG limits. For horizontal tail area to wing area ratios between .246 and .267 the forward CG limit is takeoff rotation critical while the aft CG limit is maintained 10 percent aft. The main landing gear can now be moved forward with the increasing horizontal tail area to wing area ratios. The change in CG with respect to horizontal tail area ratio required to meet the takeoff rotation requirement is greatly increased. For horizontal tail area to wing area ratios greater than .267, the forward CG limit becomes approach trim critical and the aft CG limit is still 10 percent aft and nose wheel steering critical. Also shown in Figure 31 are the CG's corresponding to the maximum gross weight and operating weight empty for the 150 passenger, 2,500-foot field length EBF configuration with the wing located relative to the fuselage in a longitudinal position as shown in Figure 15. The weight and balance analyses are shown in Appendix D. The required horizontal tail area to wing area ratio is .390. The forward CG limit is approach trim critical and the aft CG limit is nose wheel steering critical. With this horizontal tail the static stability margin at the aft CG limit is 39 percent, far too large for good handling quality characteristics. An optimum size tail can be used if the wing is moved 89 inches forward as shown in Figure 32. The CG's corresponding to the maximum gross weight and operating weight empty are now 38.5 percent MAC and 33 percent MAC, respectively (see Appendix D). A horizontal tail area to wing area ratio of .222 is required to provide a 10 percent CG range. The forward CG limit is takeoff rotation critical and the aft CG limit is nose wheel steering critical with a static stability margin of four percent MAC.





Figure 32 EBF configuration horizontal tail sizing ~ optimum wing location

The nominal horizontal tail arm ($l_H = 875$ in.) used for the horizontal tail sizing of Figure 32 required adjustments for the 2,000 foot and 3,500 foot field length versions and required scaling for the 40 and 300 passenger versions. Figure 33 shows the influence of changing the tail arm parameter ($\frac{l_H}{\bar{c}}$) on the horizontal tail area ratio (S_H/S). Figure 33 was used to adjust the tail sizing for the 150 passenger, 2,000 foot and 3,500 foot field length versions and to size the horizontal tails for the 40 and 300 passenger versions.



Note: Dashed line represents basic 150 passenger, 2500 ft field length airplane tail size with nominal horizontal tail arm 875 in.

Figure 33 Effect of horizontal tail arm parameter ($\frac{l_H}{\bar{c}}$) on horizontal tail size ($\frac{S_H}{S}$)

8.0 CONFIGURATION DEVELOPMENT

This section contains the details of the development of the Mechanical Flap (MF) and the Externally Blown Flap (EBF) configurations. Information common to both concepts will be discussed first. This is followed by a development of the MF configuration wing geometry. The development of design constraints and sizing of the 18 airplanes in Table 5 are discussed.

TABLE 5 REQUIRED STOL AIRPLANES

| | | F.A.R. Field Length | | |
|--------------------|----------------------|---------------------|-----------|-----------|
| | | 2,000 Ft. | 2,500 Ft. | 3,500 Ft. |
| MF Configurations | Number of Passengers | 40 | 40 | 40 |
| | | 150 | 150 | 150 |
| | | 300 | 300 | 300 |
| EBF Configurations | Number of Passengers | 40 | 40 | 40 |
| | | 150 | 150 | 150 |
| | | 300 | 300 | 300 |

Sensitivities to gust load alleviation (GLA) cruise altitude and cruise Mach number will be presented.

8.1 MISSION

All airplanes are sized for the same mission. This mission, shown in Figure 34, consists of three unrefueled 250 NM hops, the cruise portion of which is flown at $M = .8$ at 35,000 feet. Reserve fuel is provided for a climb, cruise and descent to an alternate field 100 NM away. The alternate field cruise is at best range speed at 15,000 feet. Additional reserve fuel is available for one-half hour loiter at 30,000 feet. For sizing purposes an air maneuver time of six minutes and a ground





Figure 34 Mission

(a) Plan and profile views



(b) Front views




Figure 35 Fuselage arrangement

maneuver time of two minutes per leg was used. Time, fuel and distance to accelerate to start climb speed and from the end climb speed to $M = .8$ at 35,000 feet also influenced the sizing.

8.2 FUSELAGES

The interior arrangements are shown in Figure 35. Figure 35(a) are plan and profile views. Figure 35(b) are larger scale front views of each fuselage.

All-economy seating was assumed for all payloads on a 34 inch seat pitch. The 40 passenger seating arrangement is four abreast double seat with a single center aisle. The 150 passenger fuselage is a six abreast double seat arrangement separated by two aisles, while the 300 passenger airplanes have an eight abreast double seat configuration separated by two aisles and a large console type armrest down the centerline.

8.3 MECHANICAL FLAP CONFIGURATION WING DEVELOPMENT

A requirement of this study was to develop the wing geometry of the Mechanical Flap (MF) STOL airplane, that is, to optimize the geometry in terms of sweep, thickness, taper and aspect ratio to accomplish a .8 Mach cruise.

The fundamentals controlling the sweep and thickness trade are concerned with the level of supercritical wing technology. The basis for the level of technology assumed in this study is shown on Figure 11.

The wing geometry assumed at the time of the sweep/thickness trade was:

| | <u>MF</u> | <u>EBF (FIXED)</u> |
|------------------|-----------|--------------------|
| Aspect Ratio | 6 | 7.48 |
| Taper Ratio | .4 | .29 |
| $C_{L_{Design}}$ | .2 | .3 |
| M_{DD} | .81 | .81 |

The initial MF configuration wing geometry is from the feasibility study airplane of Reference 1. The EBF configuration wing geometry is fixed except for thickness.

The 2D to 3D correlating relationships referred to in Section 4.3.1 were used to determine the average chordwise thickness ratio for a series of sweep angles for the MF configuration and for a quarter chord sweep of 30° for the EBF configuration. The spanwise thickness ratio was assumed to

be distributed according to Figure 36. In this Figure $(t/c)_{av}$ is $(t/c)_{2D}$ corrected for sweep. The results of this transformation are contained in Table 6.

TABLE 6 WING THICKNESS DISTRIBUTION

| QUARTER CHORD SWEEP | MF | | | | EBF |
|---------------------------|------|------|------|------|------|
| | 10° | 15° | 20° | 25° | 30° |
| $(t/c)_{2D}$ | .146 | .152 | .164 | .182 | .189 |
| $(t/c)_{av}$ (Streamwise) | .148 | .153 | .163 | .175 | .175 |
| $(t/c)_{outbd.}$ | .129 | .133 | .142 | .152 | .152 |
| $(t/c)_{root}$ | .174 | .180 | .192 | .205 | .208 |




Figure36 Spanwise thickness

The average thickness ratio is shown on Figure 37(a). The EBF configuration data point does not fit the trend because it has a different planform than the MF configuration.




Figure 37 Sweep/thickness trade

The figure of merit used to determine the best wing geometry in terms of sweep and thickness was the wing structural box weight. Figure 37(b) contains the results of this study. Class I weight estimation methods were used to calculate the wing structural box trends with $\Lambda_{c/4}$ and t/c . The net change is an increase in wing box weight with increasing sweep. Therefore, minimum sweep was chosen which not only provides the lightest wing box for .8 cruise Mach number but also provides higher lift at low speeds.

Optimum taper and aspect ratio were determined by sizing a 150 passenger airplane for a 2,500 foot F.A.R. field length assuming an unswept trailing edge flap hinge line and the proper wing loading, $\Lambda_{c/4}$, T/W , \bar{V}_H and t/c as taper ratio was varied for constant values of aspect ratio. The results of this work are shown on Figure 38. These data indicate that the lightest airplane would have an aspect ratio of about 13 and taper ratio .1. However, aspect ratio 8 and taper ratio .275 were chosen for the study. There are several reasons for accepting a geometry which appears to be less than optimum.

- Structural box weight multiplier was extrapolated above aspect ratio 11.5 due to lack of empirical data for high speed wings with larger aspect ratios.
- The increase in aspect ratio from 8 to 13 is a 20 percent increase in span which impairs ground handling as well as roll response.




Figure 38 Wing planform optimization

- Wing weight actually increases above aspect ratio 7. This would imply a costlier wing especially when it is realized that the optimum taper ratio decreases with increasing aspect ratio resulting in short, thin wing tips.

The final geometry of the MF airplane wing is shown on Figure 39.

8.4 AIRPLANE PERFORMANCE AND SIZING

8.4.1 MECHANICAL FLAP CONFIGURATION DESIGN CONSTRAINTS

The design constraints for the MF configuration are shown on Figure 40. The minimum gross weight mechanical flap configuration results from the definition of maximum wing loading available and minimum installed thrust-to-weight/ratio required. Wing loading is defined by landing. Installed sea level static thrust-to-weight ratio is critical for the start cruise requirement of .8 Mach at 35,000 feet. Engine-out go-around climb limits and the landing constraint were analyzed using the low speed lift and drag polars and the installed engine data. The takeoff and start-cruise constraints were determined using computer programs. The takeoff program, described in Paragraph 5.1, requires




Figure 39 Wing - MF configuration




Figure 40 MF configuration design constraints




Figure 41 MF configuration takeoff design chart

that the low speed polars and engine data be input. The airplane sizing program (ASAMP) which determines the thrust required to cruise also estimates the high speed clean drag. Engine data as a function of altitude is input to this program.

Results from the takeoff computer program are plotted as shown on Figure 41. This curve is read at the field length of interest and that data is cross plotted on the design constraint chart of Figure 40.

8.4.2 EXTERNALLY BLOWN FLAP CONFIGURATION DESIGN CONSTRAINTS

The design constraints for the EBF configuration are shown on Figure 42. Takeoff and landing performance were analyzed by the computer programs referred to in the previous section. The takeoff and landing design curves for the EBF configuration are shown on Figures 43 and 44, respectively. The landing design curve is an outgrowth of the procedure described in Section 5.2 for the analysis of an approach and go-around with powered lift. The curves of C_L versus T/W for all engines and engine out are contained in Appendix C.

The landing performance is critical for all field lengths. Aircraft were sized for a set of wing loadings and their corresponding thrust-to-weight ratio along each landing constraint line. The locus of minimum gross weight airplanes from this analysis is noted in Figure 42.

8.5 STOL TRANSPORT SIZE COMPARISON

A summary of design constraints is shown on Figure 45. For the same field length the EBF configurations have higher wing loadings but also require higher installed thrust to weight ratio than the MF configurations.

Inputting these constraints and the horizontal and vertical tail volume coefficients derived from Sections 6.0 and 7.0 the transport size comparison of Figure 46 can be made. The EBF configurations are heavier than the MF configuration for all field lengths and payloads.

It should be pointed out that the EBF configurations are extremely sensitive to landing approach safety margins and go-around procedures. A rough indication of this is shown on Figure 47. Lines 1 and 3 correspond to the landing and takeoff constraints, respectively, shown previously on Figure 42. Line 2 is the location of the landing constraint if a combination of the approach safety margin for gusts and the go-around procedure is changed. This relaxation of rules results in a reduction of EBF airplane gross weight from 214,000 pounds to about 190,000 pounds. The MF configuration gross weight for the 2,000 foot field length is 184,000 pounds, however, this airplane approaches at $1.3V_s$ which allows about 16° of α margin for gust protection and it can meet the engine out climb gradients without a configuration change.

8.6 3-VIEWS

Nine 3-views are shown including an alternate configuration for the 2,500 foot 150 passenger MF configuration. The airplanes for which a 3-view is presented and the figure number is shown in Table 7.

TABLE 7 LOCATION OF THREE-VIEWS

| Number of Passengers | Mechanical Flap Configuration | | Externally Blown Flap Configuration | |
|-------------------------|-------------------------------|---------------------------------------|-------------------------------------|-----------|
| | F.A.R. Field Length | | F.A.R. Field Length | |
| | 2000 Feet | 2500 Feet | 2000 Feet | 2500 Feet |
| 40 | | Figure 52 | | Figure 53 |
| 150 | Figure 50 | Figure 48 Figure 56 (alternate) | Figure 51 | Figure 49 |
| 300 | | Figure 54 | | Figure 55 |

Note:

4-engine airplanes

- Landing constraint } F.A.R. field lengths
- - - Takeoff constraint }
- Start cruise limit ($M = .8$ at 35,000 ft)
- . - . Locus of minimum weight airplanes




Figure 42 EBF Configuration design constraints




Figure 43 EBF configuration takeoff design chart





Figure 44 EBF configuration landing design chart



———— Mechanical flap configuration
----- Externally blown flap configuration




Figure 45 Stol transport design constraint summary




Figure 46 Stol transport-size comparison

| | $\Delta\alpha$ All Engines | Engine Out Gradient | Configuration Change | Speed Change | Engine out Lateral Trim Drag |
|---|----------------------------------|---------------------------|-------------------------|-----------------|------------------------------------|
| ① | 15° | 0° | Yes | No | No |
| ② | 10° | -1° | Yes | Yes | No |
| ③ | Takeoff requirement | | | | |





Figure 47 EBF configuration sensitivity to engine out go-around procedure

**WING**

| AREA (AERODYNAMIC REFERENCE) | 246.01 M ² | 2446 FT ² |
|------------------------------|-----------------------|----------------------|
| ASPECT RATIO | 8.0 | |
| TAPER RATIO | .175 | |
| SWEEP @ C/4 | 9.3° | |
| DIHEDRAL | 3.0° | |
| INCIDENCE (P-OT) | 2.0° | |
| INCIDENCE (TIP) | 0° | |
| MEAN AERODYNAMIC CHORD | 6.13 M | 201.5 IN |
| THICKNESS RATIO (ROOT) | .172 | |
| THICKNESS RATIO (MID) | .180 | |
| THICKNESS RATIO (TIP) | .167 | |
| ROOT CHORD | 8.83 M | 289.8 IN |
| TIP CHORD | 2.39 M | 784.0 IN |


HORIZONTAL STABILIZER

| | | |
|------------------------|----------------------|---------------------|
| AREA | 34.63 M ² | 308 FT ² |
| ASPECT RATIO | 3.45 | |
| TAPER RATIO | .40 | |
| LEADING EDGE SWEEP | 40.0° | |
| DIHEDRAL | -3.0° | |
| MEAN AERODYNAMIC CHORD | 4.23 M | 138.8 IN |
| THICKNESS RATIO (ROOT) | .10 | |
| THICKNESS RATIO (TIP) | .10 | |
| ROOT CHORD | 5.45 M | 179.1 IN |
| TIP CHORD | 2.25 M | 738.0 IN |
| VOLUME COEFFICIENT | .169 | |

VERTICAL STABILIZER

| | | |
|------------------------|----------------------|---------------------|
| AREA | 32.61 M ² | 351 FT ² |
| ASPECT RATIO | 1.0 | |
| TAPER RATIO | 1.0 | |
| LEADING EDGE SWEEP | 43.3° | |
| MEAN AERODYNAMIC CHORD | 5.69 M | 186.8 IN |
| THICKNESS RATIO | .10 | |
| ROOT CHORD | 5.69 M | 186.8 IN |
| TIP CHORD | 5.69 M | 186.8 IN |
| VOLUME COEFFICIENT | .0490 | |


Figure 48 MF configuration STOL aircraft



150 passengers,
2500 ft. F.A.R. field length

| WING | | | | HORIZONTAL STABILIZER | | | | VERTICAL STABILIZER | | | |
|------------------------------|-----------------------|-----------------------|--|------------------------|----------------------|---------------------|--|------------------------|----------------------|---------------------|--|
| AREA (AERODYNAMIC REFERENCE) | 214.96 M ² | 231.4 FT ² | | AREA | 45.99 M ² | 495 FT ² | | AREA | 31.77 M ² | 342 FT ² | |
| ASPECT RATIO | 7.48 | | | ASPECT RATIO | 4.00 | | | ASPECT RATIO | 3.77 | | |
| TAPER RATIO | .250 | | | TAPER RATIO | .40 | | | TAPER RATIO | 1.0 | | |
| SWEEP @ C/4 | 30.0° | | | LEADING EDGE SWEEP | 40.0° | | | LEADING EDGE SWEEP | 75° | | |
| DIHEDRAL | 0° | | | DIHEDRAL | 3.0° | | | MEAN AERODYNAMIC CHORD | 42.0° | | |
| INCIDENCE (ROOT) | 2.0° | | | MEAN AERODYNAMIC CHORD | 3.60 M | 141.7 IN | | THICKNESS RATIO | 5.68 M | 233.4 IN | |
| INCIDENCE (TIP) | 0° | | | THICKNESS RATIO (ROOT) | .10 | | | THICKNESS RATIO | .10 | | |
| MEAN AERODYNAMIC CHORD | 5.85 M | 232.0 IN | | THICKNESS RATIO (TIP) | .10 | | | ROOT CHORD | 6.44 M | 233.8 IN | |
| THICKNESS RATIO (ROOT) | .208 | | | ROOT CHORD | 4.84 M | 150.7 IN | | TIP CHORD | 4.83 M | 150.2 IN | |
| THICKNESS RATIO (MAC) | .157 | | | TIP CHORD | 1.94 M | 76.3 IN | | VOLUME COEFFICIENT | .0465 | | |
| THICKNESS RATIO (TIP) | .152 | | | VOLUME COEFFICIENT | .800 | | | | | | |
| ROOT CHORD | 6.31 M | 327.0 IN | | | | | | | | | |
| TIP CHORD | 2.41 M | 98.6 IN | | | | | | | | | |


Figure 49 EBF configuration STOL aircraft



150 passengers,
2000 ft. F.A.R. field length


| WING | | HORIZONTAL STABILIZER | | VERTICAL STABILIZER | |
|------------------------------|------------------------|------------------------|------------------------|------------------------|-----------------------|
| AREA (AERODYNAMIC REFERENCE) | 406.812 M ² | AREA | 110.276 M ² | AREA | 25.370 M ² |
| ASPECT RATIO | 4.00 | ASPECT RATIO | 4.00 | ASPECT RATIO | 1.0 |
| TAPER RATIO | 0.375 | LEADING EDGE SWEEP | 40.0° | TAPER RATIO | 1.0 |
| SWEEP @ C/A | 9.98° | DIHEDRAL | -3.0° | MEAN AERODYNAMIC CHORD | 7.461 M |
| DIHEDRAL | 2.0° | MEAN AERODYNAMIC CHORD | 5.972 M | THICKNESS RATIO | 0.10 |
| INCIDENCE (TYP) | 7.900 M | THICKNESS RATIO (ROOT) | 0.10 | ROOT CHORD | 7.461 M |
| MEAN AERODYNAMIC CHORD | 7.900 M | THICKNESS RATIO (TIP) | 0.10 | TIP CHORD | 7.461 M |
| THICKNESS RATIO (ROOT) | 0.120 | ROOT CHORD | 7.501 M | VOLUME COEFFICIENT | 0.882 |
| THICKNESS RATIO (MID) | 0.127 | TIP CHORD | 2.000 M | | |
| THICKNESS RATIO (TIP) | 0.136 | VOLUME COEFFICIENT | 0.784 | | |
| ROOT CHORD | 11.186 M | | | | |
| TIP CHORD | 3.076 M | | | | |

Figure 50 MF configuration STOL aircraft





| WING | | HORIZONTAL STABILIZER | | VERTICAL STABILIZER | |
|------------------------|-----------------------|------------------------|----------------------|------------------------|-----------------------|
| AREA | 33.475 m ² | AREA | 9.070 m ² | AREA | 63.484 m ² |
| ASPECT RATIO | 2.800 | ASPECT RATIO | 4.000 | ASPECT RATIO | 3.750 |
| TAPER RATIO | 30.0° | TAPER RATIO | 40.0° | TAPER RATIO | 41.0° |
| SWEEP @ C/A | 3.0° | SWEEP @ C/A | 3.0° | SWEEP @ C/A | 41.0° |
| CHORD | 3.0° | CHORD | 3.0° | CHORD | 3.0° |
| INCIDENCE (TYP) | 7.315 m | INCIDENCE (TYP) | 7.315 m | INCIDENCE (TYP) | 7.315 m |
| MEAN AERODYNAMIC CHORD | 2.208 | MEAN AERODYNAMIC CHORD | 2.208 | MEAN AERODYNAMIC CHORD | 2.208 |
| THICKNESS RATIO (ROOT) | 12.1 | THICKNESS RATIO (ROOT) | 12.1 | THICKNESS RATIO (ROOT) | 12.1 |
| THICKNESS RATIO (TIP) | 12.1 | THICKNESS RATIO (TIP) | 12.1 | THICKNESS RATIO (TIP) | 12.1 |
| ROOT CHORD | 10.311 m | ROOT CHORD | 10.311 m | ROOT CHORD | 10.311 m |
| TIP CHORD | 2.993 m | TIP CHORD | 2.993 m | TIP CHORD | 2.993 m |
| VOLUME COEFFICIENT | 117.8 in | VOLUME COEFFICIENT | 117.8 in | VOLUME COEFFICIENT | 117.8 in |
| LEADING EDGE SWEEP | 288.8 in | LEADING EDGE SWEEP | 288.8 in | LEADING EDGE SWEEP | 288.8 in |
| TRAILING EDGE SWEEP | 288.8 in | TRAILING EDGE SWEEP | 288.8 in | TRAILING EDGE SWEEP | 288.8 in |
| THICKNESS RATIO (ROOT) | 288.8 in | THICKNESS RATIO (ROOT) | 288.8 in | THICKNESS RATIO (ROOT) | 288.8 in |
| THICKNESS RATIO (TIP) | 288.8 in | THICKNESS RATIO (TIP) | 288.8 in | THICKNESS RATIO (TIP) | 288.8 in |
| ROOT CHORD | 288.8 in | ROOT CHORD | 288.8 in | ROOT CHORD | 288.8 in |
| TIP CHORD | 288.8 in | TIP CHORD | 288.8 in | TIP CHORD | 288.8 in |
| VOLUME COEFFICIENT | 288.8 in | VOLUME COEFFICIENT | 288.8 in | VOLUME COEFFICIENT | 288.8 in |

Figure 51. EBF configuration STOL aircraft



40 passengers, 2500 ft. F.A.R. field length



WING

| AREA (AERODYNAMIC REFERENCE) | 83.145 M ² | 895 FT ² |
|------------------------------|-----------------------|---------------------|
| ASPECT RATIO | 6.00 | |
| TAPER RATIO | .275 | |
| SWEEP @ C/4 | 9.68° | |
| DIHEDRAL | 3.0° | |
| INCIDENCE (ROOT) | 2.0° | |
| INCIDENCE (TIP) | 0° | |
| MEAN AERODYNAMIC CHORD | 3.571 M | 140.6 IN |
| THICKNESS RATIO (ROOT) | .172 | |
| THICKNESS RATIO (MAC) | .130 | |
| THICKNESS RATIO (TIP) | .127 | |
| ROOT CHORD | 5.057 M | 199.1 IN |
| TIP CHORD | 1.391 M | 54.8 IN |


HORIZONTAL STABILIZER

| | | |
|------------------------|-----------------------|---------------------|
| AREA | 17.466 M ² | 188 FT ² |
| ASPECT RATIO | 3.35 | |
| TAPER RATIO | .400 | |
| LEADING EDGE SWEEP | 40.0° | |
| DIHEDRAL | -3.0° | |
| MEAN AERODYNAMIC CHORD | 2.423 M | 98.4 IN |
| THICKNESS RATIO (ROOT) | .10 | |
| THICKNESS RATIO (TIP) | .10 | |
| ROOT CHORD | 3.262 M | 128.4 IN |
| TIP CHORD | 1.305 M | 51.4 IN |
| VOLUME COEFFICIENT | .795 | |



VERTICAL STABILIZER

| | | |
|------------------------|-----------------------|-----------------------|
| AREA | 10.647 M ² | 114.6 FT ² |
| ASPECT RATIO | 1.0 | |
| TAPER RATIO | 1.0 | |
| LEADING EDGE SWEEP | 43.5° | |
| MEAN AERODYNAMIC CHORD | 3.263 M | 128.5 IN |
| THICKNESS RATIO | .10 | |
| ROOT CHORD | 3.263 M | 128.5 IN |
| TIP CHORD | 3.263 M | 128.5 IN |
| VOLUME COEFFICIENT | .0507 | |

Figure 52 MF configuration STOL aircraft



40 passengers, 2500 ft. F.A.R. field length



WING

| AREA (AERODYNAMIC REFERENCE) | 73.208 M ² | 786 FT ² |
|------------------------------|-----------------------|---------------------|
| ASPECT RATIO | 7.46 | |
| TAPER RATIO | .288 | |
| SWEEP @ C/4 | 30.0° | |
| DIHEDRAL | 0° | |
| INCIDENCE (ROOT) | 2.0° | |
| INCIDENCE (TIP) | 0° | |
| MEAN AERODYNAMIC CHORD | 3.447 M | 136.7 IN |
| THICKNESS RATIO (ROOT) | .208 | |
| THICKNESS RATIO (MAC) | .157 | |
| THICKNESS RATIO (TIP) | .152 | |
| ROOT CHORD | 4.838 M | 191.3 IN |
| TIP CHORD | 1.400 M | 55.1 IN |

HORIZONTAL STABILIZER

| | | |
|------------------------|-----------------------|-----------------------|
| AREA | 15.561 M ² | 171.8 FT ² |
| ASPECT RATIO | 4.00 | |
| TAPER RATIO | .400 | |
| LEADING EDGE SWEEP | 40.0° | |
| DIHEDRAL | -3.0° | |
| MEAN AERODYNAMIC CHORD | 2.120 M | 83.5 IN |
| THICKNESS RATIO (ROOT) | .10 | |
| THICKNESS RATIO (TIP) | .10 | |
| ROOT CHORD | 2.854 M | 112.3 IN |
| TIP CHORD | 1.141 M | 44.9 IN |
| VOLUME COEFFICIENT | .836 | |


VERTICAL STABILIZER

| | | |
|------------------------|-----------------------|-----------------------|
| AREA | 10.981 M ² | 118.2 FT ² |
| ASPECT RATIO | 1.0 | |
| TAPER RATIO | 1.0 | |
| LEADING EDGE SWEEP | 42.0° | |
| MEAN AERODYNAMIC CHORD | 3.336 M | 131.4 IN |
| THICKNESS RATIO | .10 | |
| ROOT CHORD | 3.767 M | 149.1 IN |
| TIP CHORD | 2.840 M | 111.8 IN |
| VOLUME COEFFICIENT | .0671 | |

Figure 53 EBF configuration STOL aircraft

| HORIZONTAL STABILIZER | | VERTICAL STABILIZER | |
|------------------------|------------------------|------------------------|------------------------|
| AREA | 394.6 FT ² | AREA | 118.4 FT ² |
| ASPECT RATIO | 938.848 M ² | ASPECT RATIO | 110.016 M ² |
| TAPER RATIO | .178 | TAPER RATIO | 3.00 |
| SWEEP & C/A | 8.84° | TAPER RATIO | 3.00 |
| DIBENDAL | 0° | LEADING EDGE SWEEP | 40.0° |
| INCIDENCE (DEGT) | 1.0° | DIBENDAL | -3.0° |
| MEAN AERODYNAMIC CHORD | 0.066 M | MEAN AERODYNAMIC CHORD | 6.076 M |
| THICKNESS RATIO (ROOT) | .172 | THICKNESS RATIO (ROOT) | .10 |
| THICKNESS RATIO (MAC) | .180 | THICKNESS RATIO (TIP) | .10 |
| THICKNESS RATIO (TIP) | .187 | TIP CHORD | 3.174 M |
| TIP CHORD | 13.838 M | TIP CHORD | 312.2 M |
| VOLUME COEFFICIENT | 3.351 M ³ | VOLUME COEFFICIENT | .781 |
| TIP CHORD | 129.0 MM | | |

Figure 54 MF configuration STOL aircraft



| WING | | AREA (AERODYNAMIC REFERENCE) | | HORIZONTAL STABILIZER | | VERTICAL STABILIZER | |
|------------------------|------------------------|------------------------------|------------------------|------------------------|---------------------|------------------------|---------------------|
| ASPECT RATIO | 459.870 M ² | 459.870 M ² | 459.870 M ² | ASPECT RATIO | 665 FT ² | ASPECT RATIO | 665 FT ² |
| TAPER RATIO | 7.48 | 7.48 | 7.48 | TAPER RATIO | 4.00 | TAPER RATIO | 4.00 |
| SWEEP @ 1/4 | 30.0° | 30.0° | 30.0° | LEADING EDGE SWEEP | 40.0° | LEADING EDGE SWEEP | 40.0° |
| SWEEP @ 3/4 | 30.0° | 30.0° | 30.0° | TRAILING EDGE SWEEP | 30.0° | TRAILING EDGE SWEEP | 30.0° |
| INCIDENCE (TYP) | 0.533 M | 0.533 M | 0.533 M | MEAN AERODYNAMIC CHORD | 9.051 M | MEAN AERODYNAMIC CHORD | 9.051 M |
| THICKNESS RATIO (ROOT) | 15.7 | 15.7 | 15.7 | THICKNESS RATIO (TIP) | 10.0 | THICKNESS RATIO (TIP) | 10.0 |
| THICKNESS RATIO (MID) | 15.7 | 15.7 | 15.7 | ROOT CHORD | 9.800 M | ROOT CHORD | 9.800 M |
| THICKNESS RATIO (TIP) | 15.7 | 15.7 | 15.7 | TIP CHORD | 5.780 M | TIP CHORD | 5.780 M |
| THICKNESS RATIO (TIP) | 15.7 | 15.7 | 15.7 | VOLUME COEFFICIENT | .057 | VOLUME COEFFICIENT | .057 |
| THICKNESS RATIO (TIP) | 15.7 | 15.7 | 15.7 | | | | |

Figure 55 EBF configuration STOL aircraft




Figure 56 MF configuration STOL aircraft (overwing engine installation)

The 150 passenger, 2,500 foot MF alternate configuration of Figure 56 was not actually sized. The MF configuration on Figure 48 is representative of the geometry described to ASAMP for the purpose of drag and weight. The alternate configuration simply has the same general dimensions but the wing-mounted engines were moved over the wing (OTW). The major advantage of the alternate configuration lies in the possible noise reduction due to shielding of the engines by the wing. Recent studies by Boeing also indicate that lower drag and weight may be realized. This arrangement seems to have many interesting possibilities.

For every MF configuration 3-view there is an EBF configuration 3-view for the same field length and payload to allow a one-for-one size comparison. The payload series were drawn for the 2,500 foot F.A.R. field length to assure that the component parts would "fit" together reasonably. The 2,000 foot F.A.R. field length, 150 passenger airplanes were drawn for the same purpose with the additional objective to determine the engine clearance and position peculiarities as well as the tail sizes. The 3,500 foot F.A.R. field lengths were not drawn since they are similar to conventional airplanes.

8.7 SENSITIVITY STUDIES

8.7.1 GUST LOAD ALLEVIATION

Gross weight reductions to the 150 passenger airplanes provided by gust load alleviation (GLA) are shown on Figure 57. It is extremely advantageous to incorporate a GLA system on the MF airplanes capable of operation from F.A.R. field lengths less than about 2,500 feet. For the 2,000 foot F.A.R. field length the MF configuration is 43 percent lighter with GLA whereas the EBF configuration would only be about 11 percent lighter. A sensitivity to design without GLA is overlaid on the original gross weight comparison chart and shown on Figure 58. Without GLA the EBF configuration would be the lighter airplane for F.A.R. field lengths less than 2,400 feet.

Figure 59 illustrates the most critical requirements from the 18 percent chord full span trailing edge flap segment to alleviate gust loads. The lowest wing loading airplane is used, that is, the 150 passenger, 2,000 foot MF configuration ($W/S = 42 \text{ lbs/ft}^2$). The figure indicates that at about 180 KEAS, flap deflection is required to offset load factors in excess of 2.5 g's. At 360 KEAS just over four degrees of flap is required to reduce the gust load factor from 4.7 g's to the design load factor of 2.5 g's.

8.7.2 ALTITUDE

A sensitivity to designing the 150 passenger airplanes for cruising at altitudes other than the nominal mission altitude (35,000 feet) is shown on Figure 60. As anticipated, the 2,000 foot MF configuration was quite sensitive to cruising at altitudes less than its optimum cruise altitude of 38,000 feet. However, the penalty for cruising at the 35,000 foot nominal altitude for the design mission was less than one percent. The 2,500 foot EBF configuration demonstrated a cruise altitude sensitivity similar to the 2,500 foot MF configuration indicating a penalty of about 11 percent for designing for cruise at 20,000 feet rather than 35,000 feet. The higher wing loading airplanes are much less sensitive to being designed to cruise at altitudes other than their optimum cruise altitude.

8.7.3 CRUISE MACH NUMBER

The sensitivity to designing the 150 passenger 2,500 foot airplanes for cruising at Mach numbers other than the nominal .8 Mach number is shown on Figure 61. The procedure used to solve for the average wing thickness ratio according to the level of supercritical wing technology assumed was also used in this analysis to determine the thickness required as a function of design cruise Mach number. Specifically, the thickness value used was that which would cause the wing to reach drag divergence at .01 Mach above the design cruise Mach number.

Figure 61 indicates that at about $M = .86$ the MF and EBF configurations have the same gross weight and for Mach numbers higher than this the EBF is the lighter airplane. Wing thickness causes the MF airplanes to be more sensitive to design Mach number, however, .8 Mach appears to be a very reasonable design Mach number for the study mission for both types of airplanes.




Figure 57 Gross weight reduction provided by gust load alleviation




Figure 58 Stol transport-size comparison




Figure 59 Gust load alleviation requirements




Figure 60 Gross weight sensitivity to cruise altitude




FIGURE 61 Gross weight sensitivity to cruise Mach number

9.0 NOISE

The acoustic analysis of the turbofan powered STOL transports was conducted based on the F.A.R. Part 36 (Reference 18) measuring station locations (See Figure 62). On approach, the noise measuring point is located underneath the flight path, 1 NM from the threshold. At takeoff, the measuring station is located 3.5 NM from brake release underneath the flight path. The maximum sideline noise is determined by finding the location where the EPNL value is a maximum with the measuring station located 500 feet to the side of the flight path.




Figure 62 Noise measuring points and data requirement definitions

Additional information on community noise can be gained by developing equal noise contours or "footprints".

In predicting the acoustic characteristics of the engines, the scaling procedure used assumes that the fan tip speed remains constant and that the area and airflow sizing factors are proportional to the change in maximum thrust between the basic engine and the scaled version.

9.1 ESTIMATION METHODOLOGY

The acoustic characteristics of the turbofan engines were estimated using a noise prediction program. The program is designed to calculate the noise by components. Engine shape factor maps and propulsion maps are used to estimate the subcomponents for the fan noise (i.e., discrete tones, broadband noise and buzz saw noise). The noise due to the jet flow is separated in a component due to the secondary air stream and primary jet. Other noise components are summed together to form core noise (such as turbine noise, combustion noise, etc.). The total noise spectra is the power sum of each of the individual components. The components are predicted at a 150 foot polar arc, at

angles relative to the inlet from 10° to 160° at 10° intervals.

The reduction in sound pressure level (SPL) of an acoustic spectrum is usually referred to as applying attenuation to a baseline component spectra. The amount of attenuation for each component should be representative of the attenuation which can be realized and, thus, provide the basis for a balanced design.

The acoustic noise spectrum and airplane flight characteristics are used to determine the perceived noise level by accounting for factors such as the propagation time, the varying distance, the atmospheric attenuation corrections, and directivity index.

The air attenuation corrections considered are atmospheric absorption as a function of distance, relative humidity and temperature, and the extra ground attenuation as a function of elevation angle and distance. The variations in distance are accounted for by the spherical divergence correction which takes the form of:

$$\Delta \text{dB} = 20 \log_{10} \frac{\text{Distance corresponding to the input data}}{\text{Distance corresponding to the projected data}}$$

The corrections due to the doppler shift effect are taken from Reference 21.

The difference in the number of engines between the input and projected condition is corrected by using the relation

$$\Delta \text{dB} = 10 \log_{10} (\text{change in number of engines} + 1)$$

The relative jet velocity correction consists of a frequency shift and a change in SPL level. The frequency shift is calculated as

$$f_{v_1} = f_{v_0} \frac{(V_{\text{jet}} - V)_{v_1}}{(V_{\text{jet}} - V)_{v_0}}$$

The "0" subscript refers to the initial condition and the "1" subscript refers to the projected condition. The airplane velocity is denoted by "V".

The change in the SPL level is expressed as

$$\Delta \text{dB}_{v_1} = 80 \log_{10} \frac{(V_{\text{jet}} - V)_{v_1}}{(V_{\text{jet}} - V)_{v_0}}$$

The correction is applied to the primary jet noise only.

The conversion from measured values to subjective units is performed by converting each SPL value to the subjective NOY unit.

The perceived noise levels (PNL) are calculated at each angle by using the relation

$$PNL = 40 + 33.3 \log_{10} NOY_{max} + .15 (NOY - NOY_{max})$$

When tone irregularities are present, the PNL value is corrected to a tone corrected PNL by applying a technique which examines the adjacent bands of a SPL spectrum to determine the relative difference in sound pressure levels.

The effective perceived noise level (EPNL) is determined from a time history of the tone corrected PNL as outlined in Reference 18.

9.2 ATTENUATION

A set of rules were established for describing the growth of airplanes for the penalties of noise attenuation. These rules reflect experience gained by Boeing-Wichita on recent programs. The scaling factors are:

Nacelle Weight Multiplier = 2.0 (Doubles Nacelle Weight)

Fuel Flow Increase at Constant Thrust = 4%

Uninstalled Thrust Required = 4% Increase (airplane installed T/W maintained constant)

The 150 passenger airplanes were resized for noise treatment penalties. The gross weight increase data for noise treatment are shown in Figure 63.




Figure 63 Noise treatment penalties

The pertinent flight path information for each configuration is listed in Table 8. The inlet and aft fan attenuation spectra, Figure 64, represent an increase of 5 dB over the currently available treatment (NASA Lewis Quiet Engine Nacelle) to account for 1975 technology. The jet treatment consists of a 5 dB attenuation, whereas the turbine noise has been attenuated by 10 dB. The noise level increase, due to the under wing blowing for the EBF configuration was estimated to be 10 dB.

TABLE 8 SUMMARY OF FLIGHT PATH DATA

| CONFIGURATION | INSTALLED MAXIMUM THRUST PER ENGINE (LBS.) | T/O (AT 3.5 NM FROM B.R.) | | | APP. (AT 1 NM BEFORE T.D.) | | |
|---------------|---|---------------------------|----------------------|-----------------------------|----------------------------|----------------------|-------------------------------|
| | | ALTITUDE (FT.) | VELOCITY (FT/SEC) | CLIMB ANGLE (DEGREES) | ALTITUDE (FT.) | VELOCITY (FT/SEC) | DESCENT ANGLE (DEGREES) |
| MF 2000 | 20,270 | 3588 | 129.1 | 10.1 | 638 | 118.2 | 6. |
| MF 2500 | 15,330 | 2973 | 146.9 | 8.6 | 638 | 138.4 | 6. |
| MF 3500 | 13,430 | 2611 | 177.2 | 7.9 | 638 | 170.5 | 6. |
| EBF 2000 | 28,900 | 3386 | 129.1 | 9.5 | 638 | 118.2 | 6. |
| EBF 2500 | 19,930 | 2462 | 146.0 | 7.1 | 638 | 138.4 | 6. |
| EBF 3500 | 15,850 | 2115 | 179.0 | 6.4 | 638 | 170.5 | 6. |





Figure 64
Attenuation spectra for approach and takeoff for the inlet and fan duct

The results are presented on Figure 65. Suppressed engine footprint plots are shown. Information in the table includes areas and 500 foot sideline noise levels for the airplanes before and after suppression. The baseline data before noise treatment are shown in parenthesis. Also shown for comparison are the noise levels at the F.A.R. Part 36 measuring points.



| F.A.R. field length | 95 EPNdB footprint area ~ acres | | 500 ft maximum sideline ~ EPNdB | FAA point ~ EPNdB | |
|---|---------------------------------|-------------------|---------------------------------|-------------------|--------------|
| | App. & T/O | T/O only | | Approach | Takeoff |
| 150 passengers Mechanical flap configuration | 2000 | 580 (2,680)* | 250 (1,240) | 99 (108) | 82 (90) |
| | 2500 | 380 (2,250) | 190 (1,430) | 96 (105) | 83 (92) |
| | 3500 | 220 (1,750) | 140 (1,210) | 84 (102) | 83 (92) |
| 150 passengers Externally blown flap configuration | 2000 | 3,590 (19,470) | 2,650 (10,860) | 106 (124) | 100 (110) |
| | 2500 | 2,560 (15,180) | 2,200 (9,580) | 101 (121) | 100 (110) |
| | 3500 | 1,700 (16,580) | 1,530 (12,110) | 98 (118) | 98 (112) |

*Numbers in parenthesis refer to baseline conditions

Figure 65 Summary of acoustic analysis

10.0 DIRECT OPERATING COST

Direct operating costs (DOC) for selected point design airplanes from the set of 18 airplanes used for the sizing study are denoted in Table 9.

TABLE 9 STOL TRANSPORT DATA MATRIX

| NUMBER OF PASSENGERS | MECHANICAL FLAP F.A.R. FIELD LENGTH (FT) | | | EXTERNALLY BLOWN FLAP F.A.R. FIELD LENGTH (FT) | | |
|----------------------|---|--------------------------------|--------------------------------|---|--------------------------------|--------------------------------|
| | 2000 | 2500 | 3500 | 2000 | 2500 | 3500 |
| 40 | BASIC | BASIC DOC | BASIC | BASIC | BASIC DOC | BASIC |
| 150 | BASIC NT DOC DOC (NT) | BASIC NT DOC DOC (NT) | BASIC NT DOC DOC (NT) | BASIC NT DOC DOC (NT) | BASIC NT DOC DOC (NT) | BASIC NT DOC DOC (NT) |
| 300 | BASIC | BASIC DOC | BASIC | BASIC | BASIC DOC | BASIC |

BASIC = SIZED WITHOUT NOISE TREATMENT

NT = SIZED WITH NOISE TREATMENT

DOC = DOC'S CALCULATED FOR AIRPLANES WITHOUT NOISE TREATMENT

DOC (NT) = DOC'S CALCULATED FOR AIRPLANES WITH NOISE TREATMENT

The DOC's were calculated using modified ATA rules according to an agreement between NASA-Ames, Lockheed and McDonnell Douglas. These rules were used during the first phase of their studies entitled, "Study of Quiet Turbofan STOL Aircraft For Short-Haul Transportation". Table 10 is a listing of the adjustments to the 1967 ATA formula to account for STOL operation.

TABLE 10 D.O.C. FORMULA MODIFICATIONS

**Adjustments To 1967 ATA Cost Formula Per 1972
NASA-Ames Modification For STOL**

| | |
|--------------------------------|----------------|
| Crew pay (3-man subsonic jet) | 40% increase |
| Fuel | 11.5% increase |
| Maintenance labor rate | 50% increase |
| Airframe maintenance - hourly | 25% decrease |
| Airframe maintenance - cycle | 25% decrease |
| Engine investment spares ratio | 37.5% decrease |
| Utilization (hours/year) | 2500 |

All other ATA rules and conservatisms remained the same except for reserves. Reserve fuel is available for a one-half hour loiter at 30,000 feet, plus a climb, cruise and descent to an alternate field 100 NM away. The alternate field cruise is at best range speed at 15,000 feet.

Airframe and engine prices vary according to the curves on Figures 66 and 67, respectively. The summation of the two, accounting for number of engines, is the total airplane price. The prices are indicative of an airplane that would be used at least 3,500 block hours per year.

Typical input information for the 150 passenger, 2,500 ft. STOL airplanes for a 500 NM non-stop trip is shown in Table 11. This set of data and all DOC curves to be presented are for cruise at $M = .8$ at 35,000 feet. Weight of one passenger and baggage was assumed to be 200 lbs. and the passenger load factor was 100 percent. For DOC estimation the agreed upon annual utilization value is 2,500 block hours per year; however, as noted above, the airplane prices were based on a utilization of about 3,500 block hours per year. DOC's are presented in 1972 dollars.

A variation of DOC with range for the airplanes described in Table 11 is shown on Figure 68(a). Sensitivity to number of passengers is shown on Figure 68(b) assuming 2,500 feet F.A.R. field length capability. The sensitivity to F.A.R. field length for 150 passenger airplanes is shown on Figure 68(c). The percent DOC increase for the same airplanes with noise treatment is shown on Figure 68(d).

These trades indicate that trip distances of at least 400 NM are desirable, that 150 passengers is near optimum and that field lengths longer than 2,500 feet are more economical especially when the noise treatment penalties are considered.




Figure 66 Airframe prices




Figure 67 Engine prices

TABLE 11 DIRECT OPERATING COST INPUT

Trip Distance = 575 SM (500NM)


| | Mechanical Flap Configuration | Externally Blown Flap Configuration |
|---------------------------|-------------------------------------|---|
| No. passengers | 150 | 150 |
| F.A.R. field length (ft) | 2,500 | 2,500 |
| Total gross weight (lbs) | 148,300 | 167,800 |
| OWE (lbs) | 96,500 | 111,700 |
| Fuel capacity (lbs) | 21,800 | 26,000 |
| Total engine weight (lbs) | 7,000 | 12,100 |
| Thrust/eng. (lbs) | 15,350 | 19,900 |
| Total A/P cost (\$M) | 11 | 12.4 |
| Cost of one engine (\$M) | .467 | .500 |
| Ground {Time (hrs) | .100 | .100 |
| Maneuver {Fuel (lbs) | 120 | 225 |
| Air {Time (hrs) | .067 | .067 |
| Maneuver {Fuel (lbs) | 240 | 330 |
| Climb {Time (hrs) | .285 | .144 |
| {Fuel (lbs) | 2,740 | 2,560 |
| {Dist (NM) | 83 | 52 |
| Acceleration {Time (hrs) | .100 | .014 |
| {Fuel (lbs) | 600 | 155 |
| {Dist (NM) | 40 | 6 |
| Descent {Time (hrs) | .117 | .117 |
| {Fuel (lbs) | 330 | 390 |
| {Dist (NM) | 50 | 50 |
| Cruise {Time* (hrs) | .776 | .918 |
| {Fuel* (lbs) | 4,940 | 6,360 |
| {Dist* (NM) | 358 | 423 |
| Block Time (hrs) | 1.445 | 1.360 |
| Block Fuel (lbs) | 8,970 | 10,020 |

*Standard ATA airway distance increment and traffic allowance included


Note: M = .8 cruise at 35,000 ft

— Mechanical flap configuration


- - - Externally blown flap configuration




(a) Sensitivity to range



(b) Sensitivity to number of passengers



(c) Sensitivity to field length



(d) Sensitivity to noise treatment

Figure 68 D.O.C. trade study

11.0 CONCLUDING REMARKS

A conclusion of the feasibility study of Reference 1 was that through the use of modern control systems technology to provide ride smoothing, a low-wing-loading mechanical flap STOL airplane appears competitive with a high-wing-loading powered lift design (airplane Model 751 of Reference 1). Because powered lift was not relied upon, the resulting configuration offered advantages in system simplicity, reliability, and safety. A more significant conclusion of the present study is that through the use of an active control system for gust load alleviation, as well as for ride smoothing, and for the powered-lift airworthiness standards assumed, low-wing-loading mechanical flap airplanes are competitive with externally blown flap airplanes over a wide range of payloads and field lengths. Therefore, advantages in system simplicity, reliability, and safety can be realized regardless of the size of the airplane or the STOL field length.

For the range of field lengths and payloads investigated the MF configurations were lighter, quieter and more economical than the EBF configurations.

On the average the EBF airplanes were about 12 percent heavier than the MF airplanes for the same mission and field length.

Gust load alleviation provides a large gross weight reduction for airplanes with field lengths shorter than 2,500 feet. Without gust load alleviation the MF airplanes were heavier than the EBF airplanes for field lengths less than about 2,400 ft.

The EBF configurations are very sensitive to landing approach safety margins and go-around procedures. The EBF configuration approach speed was constrained by a requirement to have a $\Delta \alpha$ safety margin of 15 degrees for vertical gust protection at the approach power setting. Installed T/W was designed by a requirement to maintain level flight after loss of the most critical engine with the approach flap setting. As an example of the sensitivity consider a reduction of the $\Delta \alpha = 15$ degree gust margin to 10 degrees which would offer less gust protection than today's CTOL airplanes; and allow a slight descent after engine failure. The EBF airplane could approach at a lower speed (have higher wing loading) and could possibly be designed with a lower installed T/W (depends on whether or not the required go-around climb gradient becomes critical). Preliminary analyses indicate that this combination would result in an 11 percent gross weight reduction.

The MF airplanes have a $1.3V_s$ approach speed which allows 16 degrees of margin for gust protection and they can meet the engine out climb gradients without a configuration change.

The EBF configurations require more complex vertical and horizontal tails to keep the surfaces from being excessively large.

The EBF airplane maximum sideline noise is about 12 EPNdB higher than the MF airplane at 500 feet. The 95 EPNdB footprint acreage of the EBF airplane is 11 times as large as the MF airplane for takeoff and a factor of 7 larger for the summation of approach and takeoff.

The EBF airplane DOC is about 10 percent higher than the MF airplane in terms of cents per seat statute miles versus range in nautical miles. This percentage remains fairly constant for the DOC sensitivity to payload and the DOC sensitivity to field length. In addition to the above comparison cost analyses for both the MF configuration and the EBF configuration show that: trip distances less than 400 NM begin to get expensive; a 150 passenger payload and 2,500 feet F.A.R. field length are reasonable design goals.

Page intentionally left blank

12.0 APPENDICES

12.1 APPENDIX A GROUP WEIGHT STATEMENTS

Final ASAMP predicted group weight statements are presented and the locations are noted in the following table:

| Number of Passengers | F.A.R. Field Lendth | | | | | |
|-------------------------|---------------------|-------------|-------------|-------------|-------------|-------------|
| | 2000 Feet | | 2500 Feet | | 3500 Feet | |
| | MF | EBF | MF | EBF | MF | EBF |
| 40 | TABLE 12 | TABLE 13 | TABLE 14 | TABLE 15 | TABLE 16 | TABLE 17 |
| 150 | TABLE 18 | TABLE 19 | TABLE 20 | TABLE 21 | TABLE 22 | TABLE 23 |
| 300 | TABLE 24 | TABLE 25 | TABLE 26 | TABLE 27 | TABLE 28 | TABLE 29 |

TABLE 12 GROUP WEIGHT STATEMENT
MF configuration, 40 passengers, 2000 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|---|---------------|--------|------|
| PROPULSION GROUP | | WEIGHT | |
| PRIMARY ENGINES | 2970. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 186. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = | 1.00 |
| THRUST REVERSERS | 253. | | |
| FUEL SYSTEM | 310. | K21= | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 4012. | | |
| STRUCTURES GROUP | | | |
| WING | 9282. | K8 = | 1.00 |
| HORIZONTAL TAIL | 1179. | K9 = | 1.00 |
| VERTICAL TAIL | 1034. | K10= | 1.00 |
| FUSELAGE | 9425. | K11= | 1.29 |
| LANDING GEAR | 3628. | K12= | 1.58 |
| ENGINE STRUTS | 0. | K20= | 1.00 |
| ENGINE NACELLES | 435. | K14= | 1.00 |
| ENGINE DUCT | 372. | | |
| ENGINE MOUNT | 33. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 25388. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 582. | K4 = | 1.00 |
| SURFACE CONTROLS | 983. | K16= | 1.04 |
| HYDRAULICS | 805. | K17= | 1.35 |
| PNEUMATICS | 403. | K17= | 1.35 |
| ELECTRICALS | 780. | K6 = | 1.00 |
| ELECTRONICS | 983. | K7 = | 1.28 |
| FLIGHT DECK ACCOMMODATIONS | 676. | K15= | 1.00 |
| PASSENGER ACCOMMODATIONS | 1971. | | |
| CARGO ACCOMMODATION | 235. | K13= | 0.67 |
| EMERGENCY EQUIPMENT | 231. | K18= | 1.12 |
| AIR CONDITIONING | 466. | | |
| ANTI-ICING | 261. | | |
| APU | 769. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 9144. | | |
| MANUFACTURERS EMPTY WEIGHT | 38544. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 1201. | K19= | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 39746. | | |
| PAYLOAD | 8000. | | |
| FUEL | 9652. | | |
| GROSS WEIGHT | 57398. | | |

TABLE 13 GROUP WEIGHT STATEMENT
EBF configuration, 40 passengers, 2000 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|--------|--------|------|
| PROPULSION GROUP | | WEIGHT | |
| PRIMARY ENGINES | 5556. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 272. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = | 1.00 |
| THRUST REVERSERS | 956. | | |
| FUEL SYSTEM | 379. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 7521. | | |
| STRUCTURES GROUP | | | |
| WING | 8797. | K8 = | 1.00 |
| HORIZONTAL TAIL | 1859. | K9 = | 1.00 |
| VERTICAL TAIL | 1544. | K10 = | 1.00 |
| FUSELAGE | 10972. | K11 = | 1.29 |
| LANDING GEAR | 4278. | K12 = | 1.58 |
| ENGINE STRUTS | 1352. | K20 = | 1.00 |
| ENGINE NACELLES | 814. | K14 = | 1.00 |
| ENGINE DUCT | 0. | | |
| ENGINE MOUNT | 0. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 29616. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 589. | K4 = | 1.00 |
| SURFACE CONTROLS | 1379. | K16 = | 1.02 |
| HYDRAULICS | 729. | K17 = | 1.18 |
| PNEUMATICS | 384. | K17 = | 1.18 |
| ELECTRICALS | 780. | K6 = | 1.00 |
| ELECTRONICS | 918. | K7 = | 1.14 |
| FLIGHT DECK ACCOMMODATIONS | 676. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 1971. | | |
| CARGO ACCOMMODATION | 235. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 264. | K18 = | 1.12 |
| AIR CONDITIONING | 466. | | |
| ANTI-ICING | 264. | | |
| APU | 769. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 9425. | | |
| MANUFACTURERS EMPTY WEIGHT | 46562. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 1217. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 47779. | | |
| PAYLOAD | 8000. | | |
| FUEL | 11906. | | |
| GROSS WEIGHT | 67686. | | |

TABLE 14 GROUP WEIGHT STATEMENT
MF configuration, 40 passengers, 2500 ft. F. A. R. field length

| ASAMP WEIGHTS | | | |
|--|--------|--------|------|
| PROPULSION GROUP | | WEIGHT | |
| PRIMARY ENGINES | 2419. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 164. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = | 1.00 |
| THRUST REVERSERS | 39. | | |
| FUEL SYSTEM | 269. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 3184. | | |
| STRUCTURES GROUP | | | |
| WING | 5856. | K8 = | 1.00 |
| HORIZONTAL TAIL | 780. | K9 = | 1.00 |
| VERTICAL TAIL | 734. | K10 = | 1.00 |
| FUSELAGE | 9273. | K11 = | 1.29 |
| LANDING GEAR | 3168. | K12 = | 1.58 |
| ENGINE STRUTS | 0. | K20 = | 1.00 |
| ENGINE NACELLES | 354. | K14 = | 1.00 |
| ENGINE DUCT | 336. | | |
| ENGINE MOUNT | 27. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 20529. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 576. | K4 = | 1.00 |
| SURFACE CONTROLS | 984. | K16 = | 1.03 |
| HYDRAULICS | 738. | K17 = | 1.27 |
| PNEUMATICS | 355. | K17 = | 1.27 |
| ELECTRICALS | 780. | K6 = | 1.00 |
| ELECTRONICS | 898. | K7 = | 1.21 |
| FLIGHT DECK ACCOMMODATIONS | 676. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 1971. | | |
| CARGO ACCOMMODATION | 235. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 207. | K18 = | 1.12 |
| AIR CONDITIONING | 466. | | |
| ANTI-ICING | 233. | | |
| APU | 769. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 8889. | | |
| MANUFACTURERS EMPTY WEIGHT | 32602. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 1191. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 33794. | | |
| PAYLOAD | 8000. | | |
| FUEL | 8331. | | |
| GROSS WEIGHT | 50124. | | |

TABLE 15 GROUP WEIGHT STATEMENT
EBF configuration, 40 passengers, 2500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|--------|-------|------|
| PROPULSION GROUP | WEIGHT | | |
| PRIMARY ENGINES | 4123. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 227. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = | 1.00 |
| THRUST REVERSERS | 400. | | |
| FUEL SYSTEM | 315. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 5423. | | |
| STRUCTURES GROUP | | | |
| WING | 5938. | K8 = | 1.00 |
| HORIZONTAL TAIL | 834. | K9 = | 1.00 |
| VERTICAL TAIL | 778. | K10 = | 1.00 |
| FUSELAGE | 10721. | K11 = | 1.29 |
| LANDING GEAR | 3609. | K12 = | 1.58 |
| ENGINE STRUTS | 1057. | K20 = | 1.00 |
| ENGINE NACELLES | 604. | K14 = | 1.00 |
| ENGINE DUCT | 0. | | |
| ENGINE MOUNT | 0. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 23540. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 582. | K4 = | 1.00 |
| SURFACE CONTROLS | 1319. | K16 = | 1.02 |
| HYDRAULICS | 673. | K17 = | 1.13 |
| PNEUMATICS | 337. | K17 = | 1.13 |
| ELECTRICALS | 780. | K6 = | 1.00 |
| ELECTRONICS | 844. | K7 = | 1.10 |
| FLIGHT DECK ACCOMMODATIONS | 676. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 1971. | | |
| CARGO ACCOMMODATION | 235. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 230. | K18 = | 1.12 |
| AIR CONDITIONING | 488. | | |
| ANTI-ICING | 236. | | |
| APU | 769. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 9117. | | |
| MANUFACTURERS EMPTY WEIGHT | 38080. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 1202. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 39282. | | |
| PAYLOAD | 8000. | | |
| FUEL | 9817. | | |
| GROSS WEIGHT | 57099. | | |

TABLE 16 GROUP WEIGHT STATEMENT
MF configuration, 40 passengers, 3500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|--------|--------|------|
| PROPULSION GROUP | | WEIGHT | |
| PRIMARY ENGINES | 2184. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 154. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = | 1.00 |
| THRUST REVERSERS | -52. | | |
| FUEL SYSTEM | 253. | K21= | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 2831. | | |
| STRUCTURES GROUP | | | |
| WING | 3554. | K8 = | 1.00 |
| HORIZONTAL TAIL | 545. | K9 = | 1.00 |
| VERTICAL TAIL | 559. | K10= | 1.00 |
| FUSELAGE | 9185. | K11= | 1.29 |
| LANDING GEAR | 2900. | K12= | 1.58 |
| ENGINE STRUTS | 0. | K20= | 1.00 |
| ENGINE NACELLES | 320. | K14= | 1.00 |
| ENGINE DUCT | 319. | | |
| ENGINE MOUNT | 24. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 17406. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 573. | K4 = | 1.00 |
| SURFACE CONTROLS | 1027. | K16= | 1.02 |
| HYDRAULICS | 652. | K17= | 1.14 |
| PNEUMATICS | 306. | K17= | 1.14 |
| ELECTRICALS | 780. | K6 = | 1.00 |
| ELECTRONICS | 807. | K7 = | 1.11 |
| FLIGHT DECK ACCOMMODATIONS | 676. | K15= | 1.00 |
| PASSENGER ACCOMMODATIONS | 1971. | | |
| CARGO ACCOMMODATION | 235. | K13= | 0.67 |
| EMERGENCY EQUIPMENT | 193. | K18= | 1.12 |
| AIR CONDITIONING | 466. | | |
| ANTI-ICING | 210. | | |
| APU | 769. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 8665. | | |
| MANUFACTURERS EMPTY WEIGHT | 28903. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 1187. | K19= | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 30090. | | |
| PAYLOAD | 8000. | | |
| FUEL | 7799. | | |
| GROSS WEIGHT | 45889. | | |

TABLE 17 GROUP WEIGHT STATEMENT
EBF configuration, 40 passengers, 3500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|--------|------|------|
| PROPULSION GROUP | WEIGHT | | |
| PRIMARY ENGINES | 3410. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 202. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = | 1.00 |
| THRUST REVERSERS | 124. | | |
| FUEL SYSTEM | 289. | K21= | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 4383. | | |
| STRUCTURES GROUP | | | |
| WING | 3826. | K8 = | 1.00 |
| HORIZONTAL TAIL | 514. | K9 = | 1.00 |
| VERTICAL TAIL | 535. | K10= | 1.00 |
| FUSELAGE | 10590. | K11= | 1.29 |
| LANDING GEAR | 3259. | K12= | 1.58 |
| ENGINE STRUTS | 904. | K20= | 1.00 |
| ENGINE NACELLES | 499. | K14= | 1.00 |
| ENGINE DUCT | 0. | | |
| ENGINE MOUNT | 0. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 20127. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 577. | K4 = | 1.00 |
| SURFACE CONTROLS | 1329. | K16= | 1.00 |
| HYDRAULICS | 602. | K17= | 1.03 |
| PNEUMATICS | 292. | K17= | 1.03 |
| ELECTRICALS | 780. | K6 = | 1.00 |
| ELECTRONICS | 770. | K7 = | 1.03 |
| FLIGHT DECK ACCOMMODATIONS | 676. | K15= | 1.00 |
| PASSENGER ACCOMMODATIONS | 1971. | | |
| CARGO ACCOMMODATION | 235. | K13= | 0.67 |
| EMERGENCY EQUIPMENT | 212. | K18= | 1.12 |
| AIR CONDITIONING | 466. | | |
| ANTI-ICING | 213. | | |
| APU | 769. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 8892. | | |
| MANUFACTURERS EMPTY WEIGHT | 33402. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 1196. | K19= | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 34598. | | |
| PAYLOAD | 8000. | | |
| FUEL | 8972. | | |
| GROSS WEIGHT | 51570. | | |

TABLE 18 GROUP WEIGHT STATEMENT
MF configuration, 150 passengers, 2000 ft. F.A.R. field length

| ASAMP WEIGHTS | | |
|--|---------|-----------|
| PROPULSION GROUP | WEIGHT | |
| PRIMARY ENGINES | 9235. | K5 = 1.00 |
| ENGINE ACCESSORIES | 372. | K5 = 1.00 |
| ENGINE CONTROLS | 150. | K3 = 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = 1.00 |
| THRUST REVERSERS | 2672. | |
| FUEL SYSTEM | 811. | K21= 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | |
| TOTAL PROPULSION GROUP WEIGHT | 13383. | |
| STRUCTURES GROUP | | |
| WING | 41104. | K8 = 1.00 |
| HORIZONTAL TAIL | 4206. | K9 = 1.00 |
| VERTICAL TAIL | 3344. | K10= 1.00 |
| FUSELAGE | 22602. | K11= 1.29 |
| LANDING GEAR | 11623. | K12= 1.58 |
| ENGINE STRUTS | 0. | K20= 1.00 |
| ENGINE NACELLES | 2564. | K14= 1.00 |
| ENGINE DUCT | 1301. | |
| ENGINE MOUNT | 102. | |
| STRUCTURE WEIGHT INCREMENT | 0. | |
| TOTAL STRUCTURE WEIGHT | 86846. | |
| FIXED EQUIPMENT | | |
| INSTRUMENTS | 674. | K4 = 1.00 |
| SURFACE CONTROLS | 1966. | K16= 1.04 |
| HYDRAULICS | 1164. | K17= 1.35 |
| PNEUMATICS | 846. | K17= 1.35 |
| ELECTRICALS | 1560. | K6 = 1.00 |
| ELECTRONICS | 1571. | K7 = 1.28 |
| FLIGHT DECK ACCOMMODATIONS | 906. | K15= 1.00 |
| PASSENGER ACCOMMODATIONS | 9445. | |
| CARGO ACCOMMODATION | 808. | K13= 0.67 |
| EMERGENCY EQUIPMENT | 640. | K18= 1.12 |
| AIR CONDITIONING | 1862. | |
| ANTI-ICING | 404. | |
| APU | 988. | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | |
| TOTAL FIXED EQUIPMENT WEIGHT | 22834. | |
| MANUFACTURERS EMPTY WEIGHT | 123062. | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 3409. | K19= 1.00 |
| OPERATIONAL EMPTY WEIGHT | 126471. | |
| PAYLOAD | 30000. | |
| FUEL | 27442. | |
| GROSS WEIGHT | 183912. | |

TABLE 19 GROUP WEIGHT STATEMENT
EBF configuration, 150 passengers, 2000 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|--------|------|
| PROPULSION GROUP | | WEIGHT | |
| PRIMARY ENGINES | 17571. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 552. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = | 1.00 |
| THRUST REVERSERS | 5051. | | |
| FUEL SYSTEM | 980. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 24511. | | |
| STRUCTURES GROUP | | | |
| WING | 37793. | K8 = | 1.00 |
| HORIZONTAL TAIL | 6253. | K9 = | 1.00 |
| VERTICAL TAIL | 4896. | K10 = | 1.00 |
| FUSELAGE | 27444. | K11 = | 1.29 |
| LANDING GEAR | 13529. | K12 = | 1.58 |
| ENGINE STRUTS | 3497. | K20 = | 1.00 |
| ENGINE NACELLES | 4750. | K14 = | 1.00 |
| ENGINE DUCT | 0. | | |
| ENGINE MOUNT | 0. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 94161. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 696. | K4 = | 1.00 |
| SURFACE CONTROLS | 2738. | K16 = | 1.02 |
| HYDRAULICS | 1092. | K17 = | 1.18 |
| PNEUMATICS | 831. | K17 = | 1.18 |
| ELECTRICALS | 1560. | K6 = | 1.00 |
| ELECTRONICS | 1524. | K7 = | 1.14 |
| FLIGHT DECK ACCOMMODATIONS | 906. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 9445. | | |
| CARGO ACCOMMODATION | 808. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 738. | K18 = | 1.12 |
| AIR CONDITIONING | 1862. | | |
| ANTI-ICING | 436. | | |
| APU | 988. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 23623. | | |
| MANUFACTURERS EMPTY WEIGHT | 146295. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 3446. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 149741. | | |
| PAYLOAD | 30000. | | |
| FUEL | 34326. | | |
| GROSS WEIGHT | 214066. | | |

TABLE 20 GROUP WEIGHT STATEMENT
MF configuration, 150 passengers, 2500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|--------|------|
| PROPULSION GROUP | | WEIGHT | |
| PRIMARY ENGINES | 4998. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 314. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = | 1.00 |
| THRUST REVERSERS | 1816. | | |
| FUEL SYSTEM | 662. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 10084. | | |
| STRUCTURES GROUP | | | |
| WING | 23325. | K8 = | 1.00 |
| HORIZONTAL TAIL | 2578. | K9 = | 1.00 |
| VERTICAL TAIL | 2106. | K10 = | 1.00 |
| FUSELAGE | 20820. | K11 = | 1.29 |
| LANDING GEAR | 9371. | K12 = | 1.58 |
| ENGINE STRUTS | 0. | K20 = | 1.00 |
| ENGINE NACELLES | 1623. | K14 = | 1.00 |
| ENGINE DUCT | 1088. | | |
| ENGINE MOUNT | 77. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 60989. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 648. | K4 = | 1.00 |
| SURFACE CONTROLS | 1942. | K16 = | 1.03 |
| HYDRAULICS | 1000. | K17 = | 1.27 |
| PNEUMATICS | 678. | K17 = | 1.27 |
| ELECTRICALS | 1560. | K6 = | 1.00 |
| ELECTRONICS | 1329. | K7 = | 1.21 |
| FLIGHT DECK ACCOMMODATIONS | 906. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 9445. | | |
| CARGO ACCOMMODATION | 808. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 525. | K18 = | 1.12 |
| AIR CONDITIONING | 1862. | | |
| ANTI-ICING | 339. | | |
| APU | 988. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 22029. | | |
| MANUFACTURERS EMPTY WEIGHT | 93102. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 3375. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 96477. | | |
| PAYLOAD | 30000. | | |
| FUEL | 21804. | | |
| GROSS WEIGHT | 148280. | | |

TABLE 21 GROUP WEIGHT STATEMENT
EBF configuration, 150 passengers, 2500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|-------|------|
| PROPULSION GROUP | WEIGHT | | |
| PRIMARY ENGINES | 12112. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 439. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = | 1.00 |
| THRUST REVERSERS | 2501. | | |
| FUEL SYSTEM | 774. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 17184. | | |
| STRUCTURES GROUP | | | |
| WING | 23171. | K8 = | 1.00 |
| HORIZONTAL TAIL | 2700. | K9 = | 1.00 |
| VERTICAL TAIL | 2208. | K10 = | 1.00 |
| FUSELAGE | 24807. | K11 = | 1.29 |
| LANDING GEAR | 10602. | K12 = | 1.58 |
| ENGINE STRUTS | 2572. | K20 = | 1.00 |
| ENGINE NACELLES | 2454. | K14 = | 1.00 |
| ENGINE DUCT | 0. | | |
| ENGINE MOUNT | 0. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 68515. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 662. | K4 = | 1.00 |
| SURFACE CONTROLS | 2578. | K16 = | 1.02 |
| HYDRAULICS | 938. | K17 = | 1.13 |
| PNEUMATICS | 660. | K17 = | 1.13 |
| ELECTRICALS | 1560. | K6 = | 1.00 |
| ELECTRONICS | 1286. | K7 = | 1.10 |
| FLIGHT DECK ACCOMMODATIONS | 906. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 9445. | | |
| CARGO ACCOMMODATION | 808. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 588. | K18 = | 1.12 |
| AIR CONDITIONING | 1862. | | |
| ANTI-ICING | 359. | | |
| APU | 988. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 22637. | | |
| MANUFACTURERS EMPTY WEIGHT | 108336. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 3400. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 111736. | | |
| PAYLOAD | 30000. | | |
| FUEL | 26014. | | |
| GROSS WEIGHT | 167750. | | |

TABLE 22 GROUP WEIGHT STATEMENT
MF configuration, 150 passengers, 3500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|------|------|
| PROPULSION GROUP | WEIGHT | | |
| PRIMARY ENGINES | 6124. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 289. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = | 1.00 |
| THRUST REVERSERS | 1477. | | |
| FUEL SYSTEM | 603. | K21= | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 8785. | | |
| STRUCTURES GROUP | | | |
| WING | 13479. | K8 = | 1.00 |
| HORIZONTAL TAIL | 1795. | K9 = | 1.00 |
| VERTICAL TAIL | 1514. | K10= | 1.00 |
| FUSELAGE | 19940. | K11= | 1.29 |
| LANDING GEAR | 8260. | K12= | 1.58 |
| ENGINE STRUTS | 0. | K20= | 1.00 |
| ENGINE NACELLES | 1256. | K14= | 1.00 |
| ENGINE DUCT | 995. | | |
| ENGINE MOUNT | 67. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 47306. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 635. | K4 = | 1.00 |
| SURFACE CONTROLS | 2082. | K16= | 1.02 |
| HYDRAULICS | 855. | K17= | 1.14 |
| PNEUMATICS | 557. | K17= | 1.14 |
| ELECTRICALS | 1560. | K6 = | 1.00 |
| ELECTRONICS | 1148. | K7 = | 1.11 |
| FLIGHT DECK ACCOMMODATIONS | 906. | K15= | 1.00 |
| PASSENGER ACCOMMODATIONS | 9445. | | |
| CARGO ACCOMMODATION | 808. | K13= | 0.67 |
| EMERGENCY EQUIPMENT | 458. | K18= | 1.12 |
| AIR CONDITIONING | 1862. | | |
| ANTI-ICING | 293. | | |
| APU | 988. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 21607. | | |
| MANUFACTURERS EMPTY WEIGHT | 77698. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 3361. | K19= | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 81059. | | |
| PAYLOAD | 30000. | | |
| FUEL | 19638. | | |
| GROSS WEIGHT | 130697. | | |

TABLE 23 GROUP WEIGHT STATEMENT
EBF configuration, 150 passengers, 3500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|-------|------|
| PROPULSION GROUP | WEIGHT | | |
| PRIMARY ENGINES | 9631. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 382. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = | 1.00 |
| THRUST REVERSERS | 2538. | | |
| FUEL SYSTEM | 692. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 13600. | | |
| STRUCTURES GROUP | | | |
| WING | 14219. | K8 = | 1.00 |
| HORIZONTAL TAIL | 1688. | K9 = | 1.00 |
| VERTICAL TAIL | 1431. | K10 = | 1.00 |
| FUSELAGE | 23549. | K11 = | 1.29 |
| LANDING GEAR | 9206. | K12 = | 1.58 |
| ENGINE STRUTS | 7129. | K20 = | 1.00 |
| ENGINE NACELLES | 1410. | K14 = | 1.00 |
| ENGINE DUCT | 0. | | |
| ENGINE MOUNT | 0. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 53632. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 646. | K4 = | 1.00 |
| SURFACE CONTROLS | 2642. | K16 = | 1.00 |
| HYDRAULICS | 805. | K17 = | 1.03 |
| PNEUMATICS | 543. | K17 = | 1.03 |
| ELECTRICALS | 1560. | K6 = | 1.00 |
| ELECTRONICS | 1121. | K7 = | 1.03 |
| FLIGHT DECK ACCOMMODATIONS | 906. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 9445. | | |
| CARGO ACCOMMODATION | 808. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 516. | K18 = | 1.12 |
| AIR CONDITIONING | 1862. | | |
| ANTI-ICING | 309. | | |
| APU | 988. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 22151. | | |
| MANUFACTURERS EMPTY WEIGHT | 89383. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 3382. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 92765. | | |
| PAYLOAD | 30000. | | |
| FUEL | 22893. | | |
| GROSS WEIGHT | 145658. | | |

TABLE 24 GROUP WEIGHT STATEMENT
MF configuration, 300 passengers, 2000 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|--------|------|
| PROPULSION GROUP | | WEIGHT | |
| PRIMARY ENGINES | 21356. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 622. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = | 1.00 |
| THRUST REVERSERS | 4757. | | |
| FUEL SYSTEM | 1521. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 28550. | | |
| STRUCTURES GROUP | | | |
| WING | 126486. | K8 = | 1.00 |
| HORIZONTAL TAIL | 9994. | K9 = | 1.00 |
| VERTICAL TAIL | 7775. | K10 = | 1.00 |
| FUSFLAGE | 51140. | K11 = | 1.29 |
| LANDING GEAR | 27482. | K12 = | 1.58 |
| ENGINE STRUTS | 0. | K20 = | 1.00 |
| ENGINE NACELLES | 7662. | K14 = | 1.00 |
| ENGINE DUCT | 3472. | | |
| ENGINE MOUNT | 235. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 234246. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 856. | K4 = | 1.00 |
| SURFACE CONTROLS | 3165. | K16 = | 1.04 |
| HYDRAULICS | 1875. | K17 = | 1.35 |
| PNEUMATICS | 1723. | K17 = | 1.35 |
| ELECTRICALS | 2984. | K6 = | 1.00 |
| ELECTRONICS | 2737. | K7 = | 1.28 |
| FLIGHT DECK ACCOMMODATIONS | 1154. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 20576. | | |
| CARGO ACCOMMODATION | 2041. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 1452. | K18 = | 1.12 |
| AIR CONDITIONING | 3011. | | |
| ANTI-ICING | 611. | | |
| APU | 1426. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 43611. | | |
| MANUFACTURERS EMPTY WEIGHT | 306407. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 6346. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 312753. | | |
| PAYLOAD | 60000. | | |
| FUEL | 62097. | | |
| GROSS WEIGHT | 434850. | | |

TABLE 25 GROUP WEIGHT STATEMENT
EBF configuration, 300 passengers, 2000 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|-------|------|
| PROPULSION GROUP | WEIGHT | | |
| PRIMARY ENGINES | 29008. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 900. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = | 1.00 |
| THRUST REVERSERS | 7313. | | |
| FUEL SYSTEM | 1685. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 49263. | | |
| STRUCTURES GROUP | | | |
| WING | 106473. | K8 = | 1.00 |
| HORIZONTAL TAIL | 13384. | K9 = | 1.00 |
| VERTICAL TAIL | 10357. | K10 = | 1.00 |
| FUSELAGE | 60275. | K11 = | 1.29 |
| LANDING GEAR | 30035. | K12 = | 1.58 |
| ENGINE STRUTS | 6751. | K20 = | 1.00 |
| ENGINE NACELLES | 13766. | K14 = | 1.00 |
| ENGINE DUCT | 0. | | |
| ENGINE MOUNT | 0. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 241042. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 885. | K4 = | 1.00 |
| SURFACE CONTROLS | 4260. | K16 = | 1.02 |
| HYDRAULICS | 1739. | K17 = | 1.18 |
| PNEUMATICS | 1629. | K17 = | 1.18 |
| ELECTRICALS | 2984. | K6 = | 1.00 |
| ELECTRONICS | 2605. | K7 = | 1.14 |
| FLIGHT DECK ACCOMMODATIONS | 1154. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 20576. | | |
| CARGO ACCOMMODATION | 2041. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 1583. | K18 = | 1.12 |
| AIR CONDITIONING | 3011. | | |
| ANTI-ICING | 686. | | |
| APU | 1426. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 44579. | | |
| MANUFACTURERS EMPTY WEIGHT | 334884. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 6370. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 341254. | | |
| PAYLOAD | 60000. | | |
| FUEL | 73985. | | |
| GROSS WEIGHT | 475239. | | |

TABLE 26 GROUP WEIGHT STATEMENT
MF configuration, 300 passengers, 2500 ft. F.A.R. field length

| ASAMP WEIGHTS | | | |
|--|---------|-------|------|
| PROPULSION GROUP | WEIGHT | | |
| PRIMARY ENGINES | 15070. | K5 = | 1.00 |
| ENGINE ACCESSORIES | 502. | K5 = | 1.00 |
| ENGINE CONTROLS | 150. | K3 = | 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = | 1.00 |
| THRUST REVERSERS | 4095. | | |
| FUEL SYSTEM | 1234. | K21 = | 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | | |
| TOTAL PROPULSION GROUP WEIGHT | 21194. | | |
| STRUCTURES GROUP | | | |
| WING | 64099. | K8 = | 1.00 |
| HORIZONTAL TAIL | 5484. | K9 = | 1.00 |
| VERTICAL TAIL | 4331. | K10 = | 1.00 |
| FUSELAGE | 45839. | K11 = | 1.29 |
| LANDING GEAR | 20415. | K12 = | 1.58 |
| ENGINE STRUTS | 0. | K20 = | 1.00 |
| ENGINE NACELLES | 5018. | K14 = | 1.00 |
| ENGINE DUCT | 2827. | | |
| ENGINE MOUNT | 166. | | |
| STRUCTURE WEIGHT INCREMENT | 0. | | |
| TOTAL STRUCTURE WEIGHT | 148179. | | |
| FIXED EQUIPMENT | | | |
| INSTRUMENTS | 775. | K4 = | 1.00 |
| SURFACE CONTROLS | 3031. | K16 = | 1.03 |
| HYDRAULICS | 1466. | K17 = | 1.27 |
| PNEUMATICS | 1253. | K17 = | 1.27 |
| ELECTRICALS | 2984. | K6 = | 1.00 |
| ELECTRONICS | 2096. | K7 = | 1.21 |
| FLIGHT DECK ACCOMMODATIONS | 1154. | K15 = | 1.00 |
| PASSENGER ACCOMMODATIONS | 20576. | | |
| CARGO ACCOMMODATION | 2041. | K13 = | 0.67 |
| EMERGENCY EQUIPMENT | 1090. | K18 = | 1.12 |
| AIR CONDITIONING | 3011. | | |
| ANTI-ICING | 479. | | |
| APU | 1426. | | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | | |
| TOTAL FIXED EQUIPMENT WEIGHT | 41383. | | |
| MANUFACTURERS EMPTY WEIGHT | 210755. | | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 6292. | K19 = | 1.00 |
| OPERATIONAL EMPTY WEIGHT | 217048. | | |
| PAYLOAD | 60000. | | |
| FUEL | 45971. | | |
| GROSS WEIGHT | 323018. | | |

TABLE 27 GROUP WEIGHT STATEMENT
EBF configuration, 300 passengers, 2500 ft. F.A.R. field length

| ASAMP WEIGHTS | | |
|--|---------|------------|
| PROPULSION GROUP | WEIGHT | |
| PRIMARY ENGINES | 25010. | K5 = 1.00 |
| ENGINE ACCESSORIES | 700. | K5 = 1.00 |
| ENGINE CONTROLS | 150. | K3 = 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = 1.00 |
| THRUST REVERSERS | 6106. | |
| FUEL SYSTEM | 1386. | K21 = 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | |
| TOTAL PROPULSION GROUP WEIGHT | 34461. | |
| STRUCTURES GROUP | | |
| WING | 61841. | K8 = 1.00 |
| HORIZONTAL TAIL | 5575. | K9 = 1.00 |
| VERTICAL TAIL | 4419. | K10 = 1.00 |
| FUSFLAGE | 54137. | K11 = 1.20 |
| LANDING GEAR | 22680. | K12 = 1.58 |
| ENGINE STRUTS | 4317. | K20 = 1.00 |
| ENGINE NACELLES | 8257. | K14 = 1.00 |
| ENGINE DUCT | 0. | |
| ENGINE MOUNT | 0. | |
| STRUCTURE WEIGHT INCREMENT | 0. | |
| TOTAL STRUCTURE WEIGHT | 161725. | |
| FIXED EQUIPMENT | | |
| INSTRUMENTS | 801. | K4 = 1.00 |
| SURFACE CONTROLS | 3976. | K16 = 1.02 |
| HYDPAULICS | 1389. | K17 = 1.13 |
| PNEUMATICS | 1220. | K17 = 1.13 |
| ELECTRICALS | 2984. | K6 = 1.00 |
| ELECTRONICS | 2049. | K7 = 1.10 |
| FLIGHT DECK ACCOMMODATIONS | 1154. | K15 = 1.00 |
| PASSENGER ACCOMMODATIONS | 20576. | |
| CARGO ACCOMMODATION | 2041. | K13 = 0.67 |
| EMMERGENCY EQUIPMENT | 1206. | K19 = 1.12 |
| AIR CONDITIONING | 3011. | |
| ANTI-ICING | 531. | |
| APU | 1426. | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | |
| TOTAL FIXED EQUIPMENT WEIGHT | 42364. | |
| MANUFACTURERS EMPTY WEIGHT | 238549. | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 6322. | K19 = 1.00 |
| OPERATIONAL EMPTY WEIGHT | 244871. | |
| PAYLOAD | 60000. | |
| FUEL | 53980. | |
| GROSS WEIGHT | 359860. | |

TABLE 28 GROUP WEIGHT STATEMENT
MF configuration, 300 passengers, 3500 ft. F.A.R. field length

| ASAMP WEIGHTS | | |
|--|---------|-----------|
| PROPULSION GROUP | WEIGHT | |
| PRIMARY ENGINES | 12828. | K5 = 1.00 |
| ENGINE ACCESSORIES | 455. | K5 = 1.00 |
| ENGINE CONTROLS | 150. | K3 = 1.00 |
| ENGINE STARTING SYSTEM | 143. | K2 = 1.00 |
| THRUST REVERSERS | 3689. | |
| FUEL SYSTEM | 1102. | K21= 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | |
| TOTAL PROPULSION GROUP WEIGHT | 18367. | |
| STRUCTURES GROUP | | |
| WING | 35218. | K8 = 1.00 |
| HORIZONTAL TAIL | 3657. | K9 = 1.00 |
| VERTICAL TAIL | 2940. | K10= 1.00 |
| FUSLAGE | 43475. | K11= 1.29 |
| LANDING GEAR | 17325. | K12= 1.58 |
| ENGINE STRUTS | 0. | K20= 1.00 |
| ENGINE NACELLES | 4075. | K14= 1.00 |
| ENGINE DUCT | 2566. | |
| ENGINE MOUNT | 141. | |
| STRUCTURE WEIGHT INCREMENT | 0. | |
| TOTAL STRUCTURE WEIGHT | 109396. | |
| FIXED EQUIPMENT | | |
| INSTRUMENTS | 739. | K4 = 1.00 |
| SURFACE CONTROLS | 3243. | K16= 1.02 |
| HYDRAULICS | 1199. | K17= 1.14 |
| PNEUMATICS | 980. | K17= 1.14 |
| ELECTRICALS | 2984. | K6 = 1.00 |
| ELECTRONICS | 1726. | K7 = 1.11 |
| FLIGHT DECK ACCOMMODATIONS | 1154. | K15= 1.00 |
| PASSENGER ACCOMMODATIONS | 20576. | |
| CARGO ACCOMMODATION | 2041. | K13= 0.67 |
| EMERGENCY EQUIPMENT | 932. | K18= 1.12 |
| AIR CONDITIONING | 3011. | |
| ANTI-ICING | 401. | |
| APU | 1426. | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | |
| TOTAL FIXED EQUIPMENT WEIGHT | 40412. | |
| MANUFACTURERS EMPTY WEIGHT | 168175. | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 6265. | K19= 1.00 |
| OPERATIONAL EMPTY WEIGHT | 174440. | |
| PAYLOAD | 60000. | |
| FUEL | 39688. | |
| GROSS WEIGHT | 274128. | |

TABLE 29 GROUP WEIGHT STATEMENT
EBF configuration, 300 passengers, 3500 ft. F.A.R. field length

| ASAMP WEIGHTS | | |
|---|----------------|------------------|
| PROPULSION GROUP | WEIGHT | |
| PRIMARY ENGINES | 20207. | K5 = 1.00 |
| ENGINE ACCESSORIES | 601. | K5 = 1.00 |
| ENGINE CONTROLS | 150. | K3 = 1.00 |
| ENGINE STARTING SYSTEM | 208. | K2 = 1.00 |
| THRUST REVERSERS | 5472. | |
| FUEL SYSTEM | 1246. | K21= 1.00 |
| PROPULSION WEIGHT INCREMENT | 0. | |
| TOTAL PROPULSION GROUP WEIGHT | 27880. | |
| STRUCTURES GROUP | | |
| WING | 26874. | KR = 1.00 |
| HORIZONTAL TAIL | 3449. | K9 = 1.00 |
| VERTICAL TAIL | 2781. | K10= 1.00 |
| FUSELAGE | 51221. | K11= 1.29 |
| LANDING GEAR | 19310. | K12= 1.58 |
| ENGINE STRUTS | 3923. | K20= 1.00 |
| ENGINE RACELLES | 5857. | K14= 1.00 |
| ENGINE DUCT | 0. | |
| ENGINE MOUNT | 0. | |
| STRUCTURE WEIGHT INCREMENT | 0. | |
| TOTAL STRUCTURE WEIGHT | 123414. | |
| FIXED EQUIPMENT | | |
| INSTRUMENTS | 762. | K4 = 1.00 |
| SURFACE CONTROLS | 4096. | K16= 1.00 |
| HYDRAULICS | 1151. | K17= 1.03 |
| PNEUMATICS | 970. | K17= 1.03 |
| ELECTRICALS | 2984. | K6 = 1.00 |
| ELECTRONICS | 1719. | K7 = 1.03 |
| FLIGHT DECK ACCOMMODATIONS | 1154. | K15= 1.00 |
| PASSENGER ACCOMMODATIONS | 20576. | |
| CARGO ACCOMMODATION | 2041. | K13= 0.67 |
| EMERGENCY EQUIPMENT | 1034. | K1A= 1.12 |
| AIR CONDITIONING | 3011. | |
| ANTI-ICING | 440. | |
| APU | 1426. | |
| FIXED EQUIP. WEIGHT INCREMENT | 0. | |
| TOTAL FIXED EQUIPMENT WEIGHT | 41363. | |
| MANUFACTURERS EMPTY WEIGHT | 192657. | |
| WEIGHT OF STANDARD AND OPERATIONAL ITEMS | 6295. | K10= 1.00 |
| OPERATIONAL EMPTY WEIGHT | 198952. | |
| PAYLOAD | 60000. | |
| FUEL | 46583. | |
| GROSS WEIGHT | 305535. | |

12.2 APPENDIX B HIGH SPEED DRAG POLARS

Final ASAMP predicted high speed drag polars are presented and the locations are noted in the following table:

| Number of Passengers | F.A.R. Field Length | | | | | |
|-------------------------|---------------------|--------------|--------------|--------------|--------------|--------------|
| | 2000 Feet | | 2500 Feet | | 3500 Feet | |
| | MF | EBF | MF | EBF | MF | EBF |
| 40 | FIGURE 69 | FIGURE 70 | FIGURE 71 | FIGURE 72 | FIGURE 73 | FIGURE 74 |
| 150 | FIGURE 75 | FIGURE 76 | FIGURE 77 | FIGURE 78 | FIGURE 79 | FIGURE 80 |
| 300 | FIGURE 81 | FIGURE 82 | FIGURE 83 | FIGURE 84 | FIGURE 85 | FIGURE 86 |




Figure 69 High speed drag polar
MF configuration, 40 passengers, 2000 ft. F.A.R. field length




Figure 70 High speed drag polar
EBF configuration, 40 passengers, 2000 ft. F.A.R. field length




Figure 71 High speed drag polar
MF configuration, 40 passengers, 2500 ft. F.A.R. field length




Figure 72 High speed drag polar
EBF configuration, 40 passengers, 2500 ft. F.A.R. field length




Figure 73 High speed drag polar
MF configuration, 40 passengers, 3500 ft. F.A.R. field length




Figure 74 High speed drag polar
EBF configuration, 40 passengers, 3500 ft. F.A.R. field length




Figure 75 High speed drag polar
MF configuration, 150 passengers, 2000 ft. F.A.R. field length




Figure 76 High speed drag polar
EBF configuration, 150 passengers, 2000 ft. F.A.R. field length




Figure 77 High speed drag polar
MF configuration, 150 passengers, 2500 ft. F.A.R. field length




Figure 78 High speed drag polar
EBF configuration, 150 passengers, 2500 ft. F.A.R. field length




Figure 79 High speed drag polar
MF configuration, 150 passengers, 3500 ft. F.A.R. field length




Figure 80 High speed drag polar
EBF configuration, 150 passengers, 3500 ft. F.A.R. field length




Figure 81 High speed drag polar
MF configuration, 300 passengers, 2000 ft. F.A.R. field length




Figure 82 High speed drag polar
EBF configuration, 300 passengers, 2000 ft. F.A.R. field length




Figure 83 High speed drag polar
MF configuration, 300 passengers, 2500 ft. F.A.R. field length




Figure 84 High speed drag polar
EBF configuration, 300 passengers, 2500 ft. F.A.R. field length




Figure 85 High speed drag polar
MF configuration, 300 passengers, 3500 ft. F.A.R. field length




Figure 86 High speed drag polar
EBF configuration, 300 passengers, 3500 ft. F.A.R. field length

12.3 APPENDIX C DETERMINATION OF EBF WING LOADING AND THRUST TO WEIGHT

The step by step determination of the optimum wing loading (W/S) and thrust to weight ratios (T/W) for landing and approach for a given field length airplane is outlined in the following Section.

The rules in terms of landing gradients and margins are presented in Section 5.2. This Section will present the actual numbers and plots for the baseline EBF configurations. As discussed in Section 4.3.4 the low speed aerodynamic data for the EBF configuration with and without an engine out were defined for flap settings of 15° , 25° , 35° and 45° . These aerodynamic data with the appropriate engine data were input to the gradient and margin computer program. Output from this program is presented by Figure 87(a) through 87(d) for flap settings of 15° , 25° , 35° and 45° , respectively. The all engine data are presented on the left portion of the figures and the engine out data on the right portion of each figure. Examination of these data in light of the rules presented in Paragraph 5.2 reveal that at $\Delta\alpha = 15^\circ$ the all engine approach power setting is the limiting (maximum) usable approach lift coefficient for all approach flap settings. For a given W/S, the

approach speed is thus defined, $V_{APP} = \sqrt{\frac{W/S}{2\rho C_{L_{APP}}}}$ for each flap setting. Figure

18 presents the F.A.R. landing field length as a function of V_{APP} . Utilizing these data, the F.A.R. field length for each flap setting and W/S is defined.

Definition of the required design T/W for each approach flap setting is the greater of:


- All engine climb gradient = .032
 - Engine out climb gradient = 0
- } approach
flap
setting

or

- Engine out climb gradient = .027
- } go-around flap setting



See Section 5.2 for discussion of configuration change for go-around.

Based on these criteria a go-around flap setting was determined by allowing the approach flap setting to be reduced until the required engine out T/W for a climb gradient of .027 at the approach lift coefficient was equal to or less than the T/W required to maintain a level flight path ($\gamma = 0^\circ$) at the approach flap setting, while maintaining all other margins. This allows the sink rate to be arrested while the flaps are retracted to the go-around setting at constant airspeed. Determination of the go-around flap setting and required minimum T/W is a search process and requires cross plotting. The results are summarized in Table 30 for each assumed approach flap setting (Reference Figures 87(a) through 87(d)).



(a) $\delta_F = 15^\circ$

Figure 87 EBF configuration approach margins and gradients



(b) $\delta_F = 25^\circ$

Figure 87 (continued)




(c) $\delta_F = 35^\circ$

Figure 87 (continued)



(d) $\delta_F = 45^\circ$

Figure 87 (concluded)

TABLE 30 EBF CONFIGURATION LIFT AND THRUST CONSTRAINTS

| (δ_F) APPROACH | $C_{L\text{APPROACH}}$ | $(T/W)^1$ | $(TW)^2$ | (δ_F) GO-AROUND | $(T/W)^3$ |
|-----------------------|------------------------|-----------|----------|------------------------|-----------|
| 15° | 1.78 | .315 | .355 | 15° | .355 |
| 25° | 2.26 | .350 | .400 | 20° | .380 |
| 35° | 2.78 | .430 | .490 | 31° | .430 |
| 45° | 3.45 | .555 | .620 | 40° | .555 |

$(T/W)^1$ — Engine out T/W required for $\gamma = 0^\circ$ at the approach flap setting

$(T/W)^2$ — Engine out T/W required for climb gradient = .027 at approach flap setting (no configuration change allowed for engine out go-around)

$(T/W)^3$ — Engine out T/W required for climb gradient = .027 at go-around flap setting

Based on these data the FAR field length as a function of design T/W (approach flap setting) can be presented as in Figure 88. From these data the various combinations of W/S and corresponding T/W for given field lengths can be determined. These data are presented on Figure 89 for field lengths of 2,000, 2,500, and 3,500 feet. For a given field length many different combinations of W/S and T/W are possible. Thus to achieve a given field length, there exists a trade off between W/S and T/W (flap setting). For a given field length the optimum configuration was defined as the lightest gross weight configuration to perform the design mission.

Pertinent approach and go-around data for the EBF configurations are presented on Figure 90. The go-around thrust coefficient is referenced to the all engine gross thrust.

12.4 APPENDIX D WEIGHT AND BALANCE

Weight and balance CG determinations for the 150 passenger, 2,500 foot field length MF and EBF aircraft are shown in Tables 31 and 32 respectively.




Figure 88 EBF configuration landing design chart

Note:

4-engine airplanes

— Landing constraint (F.A.R. field lengths)

- - - Locus of minimum weight airplanes







Figure 89 EBF Configuration landing design constraints




(a)
Approach and
go-around
flap setting



(b)
Approach
speed



(c)
Approach
thrust



(d)
Go-around
thrust

*C_T ~ Referenced to all engine thrust
GO-AROUND

Figure 90 EBF configuration approach and landing characteristics

TABLE 31
MF CONFIGURATION CG DETERMINATION
150 PASSENGERS,
2500 FT. FIELD LENGTH

| <u>Component</u> | <u>Weight (lb)</u> | <u>Arm (in)</u> | <u>Moment (in-lb)</u> | <u>% MAC</u> |
|-------------------------------|--------------------|-----------------|-----------------------|--------------|
| Wing Engines | 8,345 | 673 | 5,616,185 | |
| Tail Engine | 4,527 | 1,325 | 5,998,275 | |
| Wing | 23,325 | 738 | 17,213,850 | |
| Horiz. Tail | 2,578 | 1,504 | 3,877,312 | |
| Vert. Tail | 2,106 | 1,337 | 2,815,722 | |
| Fuselage | 20,820 | 640 | 13,324,800 | |
| Land. Gear | 9,371 | 586 | 5,491,406 | |
| Instruments | 648 | 293 | 189,864 | |
| Surface Controls | 1,942 | 800 | 1,553,600 | |
| Hydraulics | 1,000 | 681 | 681,000 | |
| Pneumatics | 678 | 547 | 370,000 | |
| Electricals | 1,560 | 371 | 578,760 | |
| Electronics | 1,329 | 347 | 461,163 | |
| F.D. Accomo | 906 | 106 | 96,036 | |
| Pass. Accomo | 9,445 | 662 | 6,252,590 | |
| Cargo | 808 | 441 | 356,328 | |
| Emerg. Equip. | 525 | 512 | 268,800 | |
| A/C | 1,862 | 744 | 1,385,328 | |
| Anti-ice | 339 | 398 | 134,922 | |
| APU | 988 | 598 | 590,824 | |
| Manufacturers Empty Weight | 93,102 | (722) | 67,257,631 | 38.9 |
| Standard & OP Items | 3,375 | 566 | 1,910,250 | |
| O.W.E. | 96,477 | (717) | 69,167,881 | 36.5 |
| Payload | 30,000 | 658 | 19,740,000 | |
| Fuel | 21,804 | 723 | 15,764,292 | |
| Max. Gross | 148,281 | (706) | 104,672,173 | 32.0 |

TABLE 32
EBF CONFIGURATION CG DETERMINATION
150 PASSENGERS,
2500 FT. FIELD LENGTH

| <u>Component</u> | <u>Weight (lb)</u> | <u>Arm (in)</u> | <u>Moment (in-lb)</u> | <u>% MAC</u> |
|-------------------------------|--------------------|-----------------|-----------------------|--------------|
| I.B. Engines | 11,105 | 331 | 3,675,755 | |
| O.B. Engines | 11,105 | 411 | 4,564,155 | |
| Wing | 23,171 | 601 | 13,925,771 | |
| Horiz. Tail | 2,700 | 1,490 | 4,023,000 | |
| Vert. Tail | 2,208 | 1,330 | 2,936,640 | |
| Fuselage | 24,807 | 637 | 15,802,059 | |
| Land. Gear | 10,602 | 448 | 4,749,696 | |
| Instruments | 662 | 293 | 193,966 | |
| Surface Controls | 2,578 | 800 | 2,062,400 | |
| Hydraulics | 936 | 681 | 637,416 | |
| Pneumatics | 660 | 547 | 361,020 | |
| Electricals | 1,560 | 371 | 578,760 | |
| Electronics | 1,286 | 347 | 446,242 | |
| F.D. Accomo. | 906 | 106 | 96,036 | |
| Pass. Accomo. | 9,445 | 662 | 6,252,590 | |
| Cargo Accomo. | 808 | 441 | 356,328 | |
| Emerg. Eq. | 588 | 512 | 301,056 | |
| A/C | 1,862 | 744 | 1,385,328 | |
| Anti-ice | 359 | 398 | 142,882 | |
| APU | 988 | 598 | 590,824 | |
| Manufacturers Empty Weight | 108,336 | (582) | 63,081,924 | 33.2 |
| Standard & OP Items | 3,400 | 566 | 1,924,400 | |
| O.W.E. | 111,736 | (582) | 65,006,324 | 33.0 |
| Payload | 30,000 | 658 | 19,740,000 | |
| Fuel | 26,014 | 581 | 15,114,134 | |
| Max. Gross | 167,750 | (595) | 99,860,458 | 38.7 |

Page intentionally left blank

13.0 REFERENCES

1. Boeing Document: Low-Wing-Loading STOL Transport Ride Smoothing Feasibility Study. D3-8514-2, 1971.
2. Holloway, R. B.; Thompson, G. O.; Rohling, W. J.: Prospects for Low-Wing-Loading STOL Transports with Ride Smoothing. Journal of Aircraft, August 1972.
3. Boeing Document: User's Manual for ASAMP, Aircraft Sizing and Mission Performance Program. D3-7949, 1968.
4. Boeing Document: Weight Prediction Manual — Class I. D6-23201TN, 1968.
5. Boeing Document: Parametric/Statistical Weight Estimating Methods (Class I). D6-15095TN, Revision C, 1972.
6. Technical Report: Control Configured Vehicles Advanced Tanker Study. ASD/XRL-72-44, 1972.
7. Boeing Document: Compatibility of Maneuver Load Control and Relaxed Static Stability. D3-8766, 1972.
8. Boeing Document: B-52 Weight and Balance Data Retrofit and Modification Kits and Technical Order. D3-1407, 1970.
9. Boeing Document: Theoretical Analyses for Transonic Airplane Model Designs. D6-9341.
10. Boeing Document: A Simple Method for Rapid Hand Calculation of the Span Loading and Induced Drag for Arbitrary Wings. D6-24204 TN.
11. De Young, J. L. and Harper, C. W.: Theoretical Symmetric Span Loading at Subsonic Speeds for Wings Having Arbitrary Planform. NACA Report 921, 1948.
12. Hoak, D. E. and Finck, R. D.: USAF Stability and Control Datcom. 1972 Revision.
13. Anon: Data Sheets. Royal Aeronautical Society, 1972 Revision
14. Boeing Document: Low Speed Aerodynamic Prediction Method. D6-26011 TN, 1970.
15. Department of Transportation, Federal Aviation Administration: Federal Aviation Regulations. Volume III, Part 25 Airworthiness Standards: Transport Category Airplanes.
16. Department of Transportation, Federal Aviation Administration: Tentative Airworthiness Standards For Powered Lift Transport Category Aircraft. Part XX, 1970.
17. Hammond, Alexander D. and Johnson, William G., Jr.: Development of Wing-Tunnel Test Techniques for Propulsion System Simulations For Use in Small-Scale V/STOL Models. Presented at ASME Conference in San Francisco, March 1972.

18. Department of Transportation, Federal Aviation Administration: Federal Aviation Regulations. Volume III, Part 36 Noise Standards: Aircraft Type Certification.
19. The Boeing Company: Phase I Final Report for Quiet Experimental STOL Transport Research Airplane. PDR 612-1, 1972.
20. Rohling, Walter J.: Flying Qualities: An Integral Part of a Stability Augmentation System. J. Aircraft, Vol. 6, No. 6, Nov.-Dec. 1969, pp. 510-515.
21. Boeing Document: Doppler Effect Correction for Motions of Source, Observer, and Fluid. D6-17095 TN, 1966.